EQUIPMENT HAULER

See Page 15 for all Standard Features.

Spring Assist Ramp

Adjustable Coupler

- Standard Width: 82" Inside
- Fold Down Ramp
- Adjustable Coupler
- Spring Assist Ramps

HD818

Equipment Hauler Specs

	CH816	CH816SD	CH818	CH818SD	MD816	MD818	MD820	HD818-12
Bed Length	16'	16'	18'	18'	16'	18'	20'	18'
Bed Width	82"	82"	82"	82"	82"	82"	82"	82" between fenders
Bed Height	22"	22"	22"	22"	23"	23"	23"	23"
Overall Length	19' 10"	19' 10"	21' 10"	21' 10"	19' 10"	21' 10"	23' 10"	21' 10"
Overall Width	101-1/2"	101-1/2"	101-1/2"	101-1/2"	101-1/2"	101-1/2"	101-1/2"	101-1/2"
Beavertail	3'	3'	3'	3'	3'	3'	3'	3'
Axles	3.5K E-Z Lube	3.5K E-Z Lube	3.5K E-Z Lube	3.5K E-Z Lube	5.2K E-Z Lube	5.2K E-Z Lube	5.2K E-Z Lube	6K E-Z Lube
Brakes	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric both Axles
Suspension	Dbl Eye Spring	Dbl Eye Spring	Dbl Eye Spring	Dbl Eye Spring	Dbl Eye Spring	Dbl Eye Spring	Dbl Eye Spring	Slipper Leaf Spring
Wheels	5 Bolt 15"	5 Bolt 15"	5 Bolt 15"	5 Bolt 15"	6 Bolt 15"	6 Bolt 15"	6 Bolt 15"	8 Bolt 16" Silver Mod
Tires	205/75D15 "C"	205/75D15 "C"	205/75D15 "C"	205/75D15 "C"	225/75D15 "C"	225/75D15 "C"	225/75D15 "C"	245/75R16 "E"
Coupler Size	2 5/16	2 5/16	2 5/16	2 5/16	2 5/16 Adj	2 5/16 Adj	2 5/16 Adj	2 5/16 Adjustable
Jack	5000# Drop Leg	5000# Drop Leg	5000# Drop Leg	5000# Drop Leg	7000# Drop Leg	7000# Drop Leg	7000# Drop Leg	7000 lb Drop Leg
Ramps	2-54x16 Slide in	2-54x16 Slide in	2-54x16 Slide in	2-54x16 Slide in	2-54x16 Slide in	2-54x16 Slide in	2-54x16 Slide in	5' Stand Up
Stake Pockets	(8) 4 per side	(8) 4 per side	(8) 4 per side	(8) 4 per side	(8) 4 per side	(8) 4 per side	(8) 4 per side	----------
Decking	2" Treated	Dia. Plate	2" Treated	Dia Plate	2" Treated	2" Treated	2" Treated	2x10 Treated Pine
Lighting	LED	LED	LED	LED	LED	LED	LED	LED Standard
Winch Mount	Standard	Standard	Standard	Standard	Standard	Standard	Standard	----------
Steps	(2) 1 per side	(2) 1 per side	(2) 1 per side	(2) 1 per side	(2) 1 per side	(2) 1 per side	(2) 1 per side	----------

STANDARD FEATURES on Belmont Trailers

- Primed With Epoxy Primer
- Painted With Two Part Polyurethane Paint
- MIG Welded Reinforced Frame
- E-Z Lube Axles
- Safety Chains
- Factory Installed Internally Grounded Wiring Harness
- D.O.T. Approved Sealed LED Lights
- Electric Brakes on all Tandem Axles
- Safety Breakaway Kit With Battery
- Heavy Duty Drop Leg Jack (Except Single Axle Utilities)
- Adjustable Ball Hitch - 2 5/16" (10,000 GVW and up)
- Frames Welded in Fixtures
- 2x10 #1 Grade Pressure Treated Lumber

Superior Paints

- Rust Inhibiting Epoxy Primer
- Two Part Poly Paint Adds Longer Lasting Durability
- Longer Lasting Shine

Optional Colors Available by Request

Gray Red Green Yellow

UPGRADE OPTIONS

Pintle Hitch

Level Deck

Optional Mesh Ramps

Spare Tire & Mount

- Torflex Axles
- Surge Brakes
- Electric/Hydraulic Disk Brakes
- Type 27 Battery
- Radial Tire Upgrade
- Wireless Remote Available for Tilt or Dump Trailers

Belmont Machine reserves the right to change specifications and prices without prior notice.

Manufactured By:
Belmont Machine
40 Hess Road, Leola, PA 17540
Toll Free: 800.380.2404
www.belmontmachine.com