Heavy Duty Deckover 10 & 12 Ton Models

Scan for more info!

CAM SUPERLINE

www.camsuperline.com

Heavy Duty Deckover 10 & 12 Ton Models

STANDARD FEATURES

- Steel Plated Tongue
- Dexter Oil Bath Axles
- Adjustable Slipper Spring Suspension
- Hi-Tensile Steel Construction
- Full Pierced Beam Construction
- Dual 12K 2-Speed Jacks (Bolt-on)
- 6' Bi-Directional Spring Assisted Wood Filled Ramps
- Nominal 2" Oak Deck
- LED Lights – Rubber Mounted
- Adjustable Pintle Hitch
- Tool Box
- D-Ring Tie Downs (12) – 3/4"
- Mud Flaps
- Steps (4)
- Solar Charged Breakaway (Electric Brake Units)
- 7-Way RV Plug (Electric)
- 7-Way Pin Plug (Air)
- Sealed Wiring Harness
- Safety Chains (1/2" High Test)
- Epoxy Primer
- Polyurethane Paint Finish
- Colors (standard): Black, Yellow, Red, Gray, Orange, Blue, Green
- **Two Year Warranty**

102" Width Now Standard

SPECIFICATIONS

Model#	10CAM825TE	10CAM825TA	12CAM825TE	12CAM825TA
GVWR:	26,450 lbs.	26,525 lbs.	30,650 lbs.	30,725 lbs.
Empty Weight:	6,450 lbs.	6,525 lbs.	6,650 lbs.	6,725 lbs.
Payload:	20,000 lbs.	20,000 lbs.	24,000 lbs.	24,000 lbs.
Deck Length:	25' (20' Flat, 5' B/T)	25' (20' Flat, 5' B/T)	25' (20' Flat, 5' B/T)	25' (20' Flat, 5' B/T)
Overall Width:	102"	102"	102"	102"
Deck Height:	34"	34"	34"	34"
Axle Capacity:	10,000 lbs.	10,000 lbs.	12,000 lbs.	12,000 lbs.
Radial Tire Size:	235/80R16LRE	235/80R16LRE	235/80R16LRE	235/80R16LRE
Main Frame & Tongue:	12" I-Beam @ 16#	12" I-Beam @ 16#	12" I-Beam @ 16#	12" I-Beam @ 16#
Crossmembers:	3" Channel @ 4.1#	3" Channel @ 4.1#	3" Channel @ 4.1#	3" Channel @ 4.1#
Brakes:	Electric	Air w/ABS	Electric	Air w/ABS

OPTIONS AVAILABLE

- 96" Deck Width
- Extra Deck Length (32' Max)
- Gooseneck with Adjustable Coupler or King Pin and Dual 12K 2-Speed Jacks (30' Deck Max)
- Self Cleaning Beavertail and Ramps
- Double Break Beavertail (7.5') with 6' Ramps
- 30" x 80" Air Power Ramps (102" Width w/Air Brake Only)
- 40" x 80" Air Power Ramps (102" Width w/Air Brake Only)
- 36" Knife-Edge Paver Extensions (40" x 80" Air Ramps Only)
- Self-Clean Beavertail w/Pop-up Center & Self-Clean, Self-Leveling Ramp w/foot
- 61" Axle Spacing
- Wide-Track Axles
- Winch Mount
- 6' Angle Ramps
- Aluminum Wheel Simulators
- Underbody Tool Box (14"x16"x36")
- Spare Tire & Wheel
- Spare Tire Carrier (Under Bed)
- Stake Pockets and Rub Rail (96" Width Only)
- Additional D-Ring Tie-Downs – 3/4"
- Undercoating
- Custom Colors
- Galvanizing

Tongue Area w/Step

Self-Clean Beavertail w/Pop-up Center & Self-Clean, Self-Leveling Ramp w/foot (optional)

Wood Filled Ramps

Self Clean Beavertail & Ramps (optional)

Gooseneck (optional)

DEXTER AXLE

PPG

Specifications subject to change without notice.

12-14 Printed in the USA

CAM SUPERLINE

Quality. Service. Value. Dependability.

4763 Zane Miller Drive
Waynesboro, PA 17268

Toll Free: 800.378.7623
Fax: 800.279.7578

www.camsuperline.com

Heavy Duty Deckover 20 & 25 Ton Models

Scan for more info!

CAM SUPERLINE

www.camsuperline.com

Heavy Duty Deckover 20 & 25 Ton Models

STANDARD FEATURES

- Steel Plated Tongue
- Dexter Oil Bath Axles
- Hutch H-9700 Suspension
- Axle Springs: 3 Leaf (50,000 lb. Capacity)
- Spring Park Brake On All Axles
- Hi-Tensile Steel Construction
- Full Pierced Beam Construction
- Dual 50K 2-Speed Jacks (Bolt-on)
- 6' Bi-Directional Spring Assisted Wood Filled Ramps
- Nominal 2" Oak Deck
- LED Lights – Rubber Mounted
- Tool Box
- Mud Flaps
- D-Ring Tie Downs (12) – 1"
- Steps (4)
- Adjustable Pintle Hitch
- Sealed Wiring Harness
- Sealed 7-Pin Plug w/Arctic Flex Whip
- Safety Chains (5/8" High Test)
- Epoxy Primer
- Polyurethane Paint Finish
- Colors (standard): Black, Yellow, Red, Gray, Orange, Blue, Green
- **Two Year Warranty**

SPECIFICATIONS

Model#	20CAM825TA	25CAM829TA
GVWR:	51,750 lbs.	65,000 lbs.
Empty Weight:	9,095 lbs.	11,575 lbs.
Payload:	42,655 lbs.	53,425 lbs.
Deck Length:	25' (20' Flat, 5' B/T)	29' (24' Flat, 5' B/T)
Overall Width:	102"	102"
Deck Height:	35"	35"
Axle Capacity:	22,500 lbs.	22,500 lbs. (Tri-Axle)
Radial Tire Size:	235/75R17.5LRH	235/75R17.5LRH
Main Frame & Tongue:	14" I-Beam @ 22#	14" I-Beam @ 22#
Crossmembers:	5" Channel @ 6.7#	5" Channel @ 6.7#
Brakes:	Air w/ABS	Air w/ABS

OPTIONS AVAILABLE

- Extra Deck Length (32' Max)
- Air Lift Axle (25 Ton)
- Self Cleaning Beavertail and Ramps
- Double Break Beavertail (7.5') with 6' Ramps
- Air Ride Suspension
- 36" Knife-Edge Paver Extensions (40" x 80" Air Ramps Only)
- 30" x 80"; 40" x 80" Air Ramps
- Bi-Fold Air Powered Ramps NEW
- 6' Angle Ramps
- Outriggers
- Underbody Tool Box (14"x16"x36")
- Fifth Wheel Attachment w/11' Upper Deck
- Spare Tire & Wheel
- Spare Tire Carrier (Under Bed)
- Additional D-Ring Tie-Downs – 1"
- Aluminum Wheels
- Undercoating
- Custom Colors
- Galvanizing

Bi-Fold Air Powered Ramps (optional) - NEW

Air Powered Ramps (optional)

Knife-Edge Paver Extensions (optional)

Double Break Beavertail (shown with self clean option)

Fifth Wheel Attachment w/Deck (optional)

DEXTER AXLE

PPG

Specifications subject to change without notice.

12-14 Printed in the USA

CAM SUPERLINE

Quality. Service. Value. Dependability.

4763 Zane Miller Drive
Waynesboro, PA 17268

Toll Free: 800.378.7623
Fax: 800.279.7578

www.camsuperline.com