

Hi-Way[®] XT3 Type II

Multi-Purpose Dump Body

Hi-Way XT3 Type II Front Discharge Multi-Purpose Dump Body

- 1. Spreads-** Broadcast deicing materials in front of the drive tires for better traction and safety.
- 2. Hauls-** Flat dump body floor allows hauling of virtually anything, including pallets and barrels.
- 3. Dumps-** Front telescopic hoist provides low center of gravity and eliminates need for sub-frame.



Hi-Way XT3 Type II Standard Features:

- Heavy-duty 7-gauge 409 stainless steel inner and outer longitudinal sills are fully welded to the body floor to resist corrosion and improve strength.
 - 7-gauge grade 50 body sides feature “one piece” construction with radius design to reduce material build-up. Sloped top rails on side sheets and headsheets add body support and prevent debris build-up on rails.
 - 3/16” (4.8mm) AR400 conveyor floor resists bending from load impact and provides superior wear resistance.
 - Sloped tailgate allows for added capacity, providing increased closing pressure and eliminating the need for an asphalt lip which can interfere with intake hoppers on paving or chipping equipment.
 - High torque 25:1 gear case starts even the heaviest loads. Includes idler with shaft, sprockets and bearings that remove as one assembly to simplify maintenance. Forged steel sprockets ensure longer life.
 - 16.75” (43cm) wide cross conveyor handles larger capacity than auger feed or chute-style front discharge units.
 - Quick detach front spinner assembly adjusts up/down, side-to-side, and fore/aft for precise spread pattern control.
- Optional Equipment:**
- Unpainted 304 stainless steel and painted Cor-Ten[®] steel construction for added resistance to corrosion.
 - Tool boxes, stainless underbody pan, pre-wet system, screens, ladder, and conveyor cover are just some of the other options available.

XT3 Type II Specifications



Body Length	Width	CA/CT*	Body Weight (Approx.)	Struck Cap.	Struck Cap. w/Sideboards
9'/10'	95.5" (243 cm)	84" (213 cm)	3998 lbs. (1813 kg)	6.7 yds ³ (5.13 m ³)	10.0 yds ³ (7.69 m ³)
10'/11'	95.5" (243 cm)	96" (244 cm)	4183 lbs. (1900 kg)	7.5 yds ³ (5.76 m ³)	11.1 yds ³ (8.53 m ³)
11'/12'	95.5" (243 cm)	108" (274 cm)	4375 lbs. (1984 kg)	8.4 yds ³ (6.38 m ³)	12.4 yds ³ (9.44 m ³)
12'/13'	95.5" (243 cm)	108" (274 cm)	4568 lbs. (2072 kg)	9.2 yds ³ (7.01 m ³)	13.6 yds ³ (10.40 m ³)
13'/14'	95.5" (243 cm)	120" (305 cm)	4758 lbs. (2158 kg)	10.0 yds ³ (7.69 m ³)	14.8 yds ³ (11.32 m ³)
14'/15'	95.5" (243 cm)	132" (335 cm)	4948 lbs. (2299 kg)	10.8 yds ³ (8.26 m ³)	15.9 yds ³ (12.18 m ³)

*Typical Cab to Axle measurement. Please consult federal, state and local weight laws and chassis manufacturer's rating to ensure neither government weight restrictions nor the GVWR and GAWRs are exceeded.



Spinner:

The front spinner assembly adjusts up/down, side-to-side, and fore/aft for precise spread pattern control.



Body:

95.5" (243cm) wide body provides maximum capacity. Body side sheets and floor feature one-piece construction.



Hoist:

Front telescopic hoist does not require sub-frame and provides lower center of gravity when dumping. Cylinder includes 2-year warranty.



Highway Equipment Company
1330 76th Ave. SW • Cedar Rapids, IA 52404-7052
Phone: (319) 363-8281 or (800) 363-1771
Fax: (319) 286-3351 or (800) 363-8267
Online: www.highwayequipment.com
E-mail: information@highwayequipment.com

Products and specifications subject to change without notice. Photos and illustrations may or may not include optional equipment. Hi-Way® is a registered trademark of Highway Equipment Company. Copyright 2011 Highway Equipment Company, Inc. Form No. H1148-2011-12