

Hi-Way XT3 Type I Front or Rear Discharge Multi-Purpose Dump Body

- 1. Spreads-** Broadcast deicing materials at rear or front with optional front cross conveyor.
- 2. Hauls-** Flat dump body floor allows hauling of virtually anything, including pallets and barrels.
- 3. Dumps-** Front telescopic hoist provides low center of gravity and eliminates need for sub-frame.



Hi-Way XT3 Type I Standard Features:

- Heavy-duty 7-gauge 409 stainless steel inner and outer longitudinal sills are fully welded to body floor to resist corrosion and improve strength.
- 7-gauge grade 50 body sides feature one-piece construction with radius design to reduce material build-up. Sloped top rails on side sheets and headsheets add body support and prevent debris build-up on the rails.
- 3/16" (4.8mm) AR400 conveyor floor resists bending from load impact and provides superior wear resistance.
- High torque 25:1 gear case starts even the heaviest loads. Includes idler with shafts, sprockets and bearing that remove as one assembly to simplify maintenance. Dropped forged steel sprockets ensure longer life.
- Quick detach front and/or rear spinner assemblies adjust up/down, side to side, and fore/aft for precise spread pattern control.

Optional Equipment:

- 16.75" (43cm) wide cross conveyor handles larger capacity than auger feed or chute style front discharge units.
- Unpainted 304 stainless steel and painted Cor-Ten® steel construction for added resistance to corrosion.
- Pre-wet system, screens, ladder, and conveyor cover are just some of the other options available.

Optional SB3 Sandbag Filler Attachment:

- Constructed of 304 stainless steel and retrofits onto any existing XT3 Type I or III with rear discharge set-up.
- Capable of filling two 50-pound sandbags in 10 seconds.
- Offers quick and easy installation and removal.
- Features an adjustable vertical chute to accommodate varying truck heights and bag sizes as well as an adjustable 12-volt DC vibrator, which can be turned on and off with an optional control, to aid in the flow of sand through the chute.



XT3 Type I Specifications



Body Length	Width	CA/CT*	Body Weight (Approx.)	Struck Cap.	Struck Cap. w/Sideboards
9'/10'	95.5" (243 cm)	84" (213 cm)	4025 lbs. (1826 kg)	6.4 yds ³ (4.89 m ³)	9.7 yds ³ (7.42 m ³)
10'/11'	95.5" (243 cm)	96" (244 cm)	4215 lbs. (1912 kg)	7.2 yds ³ (5.51 m ³)	10.8 yds ³ (8.26 m ³)
11'/12'	95.5" (243 cm)	108" (274 cm)	4405 lbs. (1998 kg)	8.0 yds ³ (6.12 m ³)	12.0 yds ³ (9.18 m ³)
12'/13'	95.5" (243 cm)	108" (274 cm)	4595 lbs. (2084 kg)	8.8 yds ³ (6.73 m ³)	13.2 yds ³ (10.09 m ³)
13'/14'	95.5" (243 cm)	120" (305 cm)	4785 lbs. (2170 kg)	9.7 yds ³ (7.42 m ³)	14.5 yds ³ (11.09 m ³)
14'/15'	95.5" (243 cm)	132" (335 cm)	4975 lbs. (2257 kg)	10.5 yds ³ (8.03 m ³)	15.6 yds ³ (11.93 m ³)

*The Cab to Axle/Tandem dimensions are only guidelines.

Consult federal, state and local weight laws and chassis manufacturer's ratings to ensure neither government weight restrictions, nor GVWR and GAWRs are exceeded.

Other Features:



Spinner/Conveyor:

The rear spinner assembly adjusts up/down, side to side, and fore/aft for precise spread pattern control.



Hoist:

Front telescopic hoist does not require sub-frame and provides lower center of gravity when dumping. Cylinder includes 2-year warranty.



Body:

95.5" (243cm) wide body provides maximum capacity. Body side sheet and floor feature one-piece construction.



Highway Equipment Company
1330 76th Ave. SW • Cedar Rapids, IA 52404-7052
Phone: (319) 363-8281 or (800) 363-1771
Fax: (319) 286-3351 or (800) 363-8267
Online: www.highwayequipment.com
E-mail: information@highwayequipment.com

Products and specifications subject to change without notice. Photos and illustrations may or may not include optional equipment. Hi-Way® is a registered trademark of Highway Equipment Company. Copyright 2011 Highway Equipment Company, Inc. Form No. H1141-2011-12