

SPREADERS & ACCESSORIES

FISHERPLOW.COM



FISHER[®]

**For more than
70 years we've
been building plows
and spreaders for
way-makers.**

FISHER® NATION doesn't stand to the side waiting for someone else to clear a path. They go where others haven't. And the way we see it, it's our job to keep making the equipment that keeps these guys plowing forward.



PRE-WET SYSTEM ACCESSORY FOR HOPPER SPREADERS

Use Less Salt and Accelerate Melting

De-icing is where the money's at, but salt and other de-icing materials come at a cost. The FISHER® pre-wet system makes better use of your salt by activating it just before it hits the spinner. Pre-wetting salt starts a chemical reaction that allows you to melt ice faster, have greater control over where your material goes, and **reduces salt application rates by up to 30%. And that goes right to your bottom line.**



Available for All STEEL-CASTER™ Hopper Spreaders

- Available in 50-gallon kits (two 25-gallon tanks) or 100-gallon kits (two 50-gallon tanks)
- 1.5 cu yd, 2.0 cu yd and 3.0 cu yd models can accept up to two of the 50-gallon kits for a maximum capacity of 100 gallons*
- 4.5 cu yd and 6.0 cu yd models can accept up to two of the 50-gallon or 100-gallon kits for a maximum capacity of 200 gallons*
- A corrosion-resistant, fully enclosed housing protects the pump, electronics and valves from the elements

Two Control Options

The updated FLEET FLEX electric hopper spreader control for STEEL-CASTER hopper spreaders and POLY-CASTER hopper spreaders includes a pre-wet accessory button which provides simple on/off** operation, allowing the operator to choose when to apply brine while spreading. The flow rate is set manually using the valve in the pump housing.

Available for POLY-CASTER™ Hopper Spreaders

- Available in 50-gallon kits (two 25-gallon tanks)
- 1.5 cu yd, 1.8 cu yd and 2.5 cu yd models can accept up to two of the 50-gallon kits for a maximum capacity of 100 gallons*
- Compatible with all POLY-CASTER hopper spreaders manufactured February 2016 or later
- With the purchase of an additional adapter kit, any POLY-CASTER manufactured between 2009 and January 2016 can accept the pre-wet system
- A corrosion-resistant, fully enclosed housing protects the pump, electronics and valves from the elements


For operators who want additional flow control from inside the cab, a separate in-cab control option is available, featuring a flow-control dial and warning lights that alert the operator of a clog, or if the tanks are empty.

Photos shown with optional accessories.

*When using a vibrator kit with the POLY-CASTER hopper, only one of the 50-gallon kits can be used. When using a vibrator kit with the STEEL-CASTER hopper, only one of either the 50-gallon kits or the 100-gallon kits can be used.

**On STEEL-CASTER gas and hydraulic models, the on/off switch is incorporated into the master accessory harness control panel.

STANDARD FEATURES FOR ALL HOPPER SPREADERS




Dual Electric Motors

Two high-torque, 12-volt electric motors provide quiet, reliable and independent control over the conveyor and spinner mechanisms. The spinner motor is sealed inside a weather-resistant housing, protecting it from corrosion.



Dual Variable-Speed Control*

Enhanced dual variable-speed control allows you to precisely match material delivery and spread patterns to conditions. Four standard accessory buttons and a dedicated blast button provide optimum in-cab efficiency. Easy-to-understand, digital self-diagnostics alert the operator when the spreader is empty or when adjustments are needed, and LEDs make the control easy to read.



Accessory Integration*

Conveniently connect accessories directly into the hub mounted in the back of the hopper. Accessories automatically integrate with the hopper control without having to run additional wires from the front of the truck.



Pintle Chain Conveyor

One of the widest in the industry, the 16½" conveyor moves more material consistently and smoothly to help reduce bridging. The corrosion-resistant, stainless steel conveyor housing provides extra protection and durability.



Adjustable Feed Gate

An adjustable feed gate provides additional control of material flow regardless of material type, reducing waste when traveling between sites.



Spinner and Spreading Width

An extra-large, 15½" polyurethane spinner delivers a spreading width of up to 40' and provides long-lasting, corrosion-free performance.



Dump and Work Light Switches*

Operators can safely offload material or fill walk-behind spreaders by using the rear-mounted conveyor dump switches. An additional switch is provided so an accessory work light may be controlled from the cab and the rear of the hopper.



Top Screen

A steel top screen comes standard, and helps break up large chunks of de-icing material during the loading process to prevent clogging and bridging during spreader operation.

FLEETFLEX ELECTRICAL SYSTEM

FLEET FLEX technology gives you easy interchangeability between electric hopper spreaders without having to change the wiring or the controls. It provides easy operation, increased reliability, simple wiring and easy installation. Additionally, accessories automatically integrate into the control for easy plug 'n' play.

*Available on dual electric motor models only

ENGINEERED TO OWN THE ICE.

The FISHER® STEEL-CASTER™ stainless steel hopper spreaders were engineered for efficiency and designed for durability. Built with the experience of more than six decades of battling tough New England storms, the STEEL-CASTER hopper spreaders are available in six sizes, with more standard features and the latest advancements in technology, resulting in maximum material control and minimal waste.



Photos shown with optional accessories.



Corrosion-Resistant Hopper

Constructed from maintenance-free, corrosion-resistant stainless steel, the hopper is reinforced with welded joints, which wrap around for long life and protection against stress.

Innovative Chute Design

Reduce material waste with this innovative chute design that delivers material to the precise points on the spinner that cast it out and away from the truck, instead of back on your bumper.

Dual-Swing Chute Design

The dual-swing chute design opens from either side to provide easy access for maintenance or material unloading.

Circular Shutter Deflector

Maximize material control with the easy-to-adjust, circular shutter deflector that provides directional spreading while maintaining even coverage and preventing materials from going where they aren't intended to go.

Inverted V

An inverted V comes standard and helps keep sufficient material weight off of the conveyor, ensuring smooth startup and flow of material.

SIZE OPTIONS

7' 1.5 cu yd | 8' 2.0 cu yd | 9' 3.0 cu yd
9' 4.5 cu yd | 10' 4.5 cu yd | 10' 6.0 cu yd

See page 5 for hopper spreader standard features.

Power Options

In addition to the standard dual electric motors, the STEEL-CASTER™ stainless steel hopper spreader is available with gas and hydraulic power options.

Chute Assembly

For precise material application, the chute assembly can be configured for either pickup or flatbed trucks or for a dump body application, ensuring you're always spreading at the optimum height. An extended chute is standard on 9' and 10' models. An extension kit is available as an accessory only on 7' and 8' models.

Removable Chute Assembly

For convenient access to the hitch or for material off-load, the chute assembly can be removed.

Additional Standard Features

Ratchet straps and tie-down points are included for strapping the hopper to the truck. For additional safety, bolting bars are also provided to attach the hopper to the vehicle and a Center High-Mounted Stop Light (CHMSL) is standard.

ACCESSORIES

Pre-Wet System | Spill Guard Kit
Central Point Grease Kit | Work Light Kit
Strobe Light Kit | Vibrator Kit
Tie-Down Chain Kit | License Plate Kit
6" Side Extensions

POLY ⚡ **CASTER.**

CONSIDER STORMS CONQUERED.

Winter storms hit fast and hard. Fight back with the FISHER® POLY-CASTER™ hopper spreader, loaded with upgraded de-icing technology to get you in and out of the storm quickly. Enhanced controls, a convenient accessory hub and the interchangeable FLEET FLEX electrical system give you the tools you need to make the best use of your de-icing materials. Conquer every storm with the easy-to-install POLY-CASTER hopper spreader.



Photos shown with optional accessories.



Two-Piece Poly Hopper Cover

The overlapping poly hopper cover shields de-icing material from the elements. Its overlapping design seals out moisture while molded grooves direct water away from the hopper, and its domed shape increases hopper capacity. In the open position, the two cover pieces act as spill guards and protect the truck from material overflow while loading.

Chute Assembly

For precise material application, the adjustable-height chute assembly can be configured for either pickup or flatbed trucks or for a dump body application, ensuring you're always spreading at the optimum height.

Removable Chute Assembly

For convenient access to the hitch or for material off-load, the chute assembly can be removed—no tools required.

SIZE OPTIONS

7' 1.5 cu yd | 8' 1.8 cu yd | 8' 2.5 cu yd

See page 5 for hopper spreader standard features.

Corrosion-Resistant Hopper

The proven double-walled hopper is built of durable poly for corrosion-free performance, whether using rock salt, calcium chloride, sand or any other type of de-icing material.

Convenient Storage

Unlike other hoppers, the POLY-CASTER™ spreaders feature an innovative hopper design that allows it to be easily installed and removed from your vehicle. Since it can be stood up vertically, this means less storage space and more versatility within your fleet.

Additional Standard Features

Tie-down points are included for strapping the hopper to the truck. For additional safety, bolting bars are also provided to attach the hopper to the vehicle and a Center High-Mounted Stop Light (CHMSL) is standard.

ACCESSORIES

Pre-Wet System | Central Point Grease Kit
Work Light Kit | Strobe Light Kit
Stainless Steel Inverted V Kit | Vibrator Kit
Ratchet Tie-Down Kit | License Plate Kit

POLY ⚡ **CASTER** *UTV*

UTILITY EDITION.

There's no better way to apply the finishing touch to sidewalks, paths and driveways than with the FISHER® POLY-CASTER™ UTV hopper spreader. Designed specifically to fit into the bed of a UTV, the POLY-CASTER UTV hopper spreader lets you easily address the applications where only a UTV can go.



Dual Electric Motors

Two high-torque, 12-volt electric motors provide quiet, reliable, independent control over the auger and spinner mechanisms. The spinner motor is sealed inside a weather-resistant housing, protecting it from corrosion.

Dual Variable-Speed Control

Independently control two electric motors to precisely match material delivery and spread pattern to conditions. A switch to run the vibrator is integrated into the control for operator convenience.

Material Delivery

Material is delivered by a heavy-duty steel auger. If an obstruction occurs, the transverse auger system helps reduce downtime by automatically reversing until the obstruction is cleared.

Inverted V / Vibrator

The inverted V helps keep material weight off the auger, ensuring smooth startup and flow of material. It is directly connected to the vibrator to reduce bridging and keep material moving to the auger.

Spinner and Spreading Width

Durable, 12" corrosion-free spinner delivers a spreading width of up to 30' and features top and bottom guards that protect the spinner from damage if backed into a solid object.

Quick-Connect Spinner / Chute Assemblies

Gain easy access to the hitch by removing the quick-connect spinner drive and chute assemblies.

Corrosion-Resistant Hopper

One-piece hopper is built of durable poly for corrosion-free performance.

Top Screen

A steel top screen helps break up large chunks of de-icing material during the loading process to prevent clogging and bridging during spreader operation.

Cover

A custom-fitted tarp cover helps to keep your ice control material dry and prevent clumping.

Ratchet Straps

The nylon ratchet straps provide additional in-bed stability and security.

SIZE OPTIONS

64" | 11.0 cu ft

ACCESSORIES

Auger Tube Restrictor Kit | Optimum Flow Kit

LOW PROFILE

CLEARLY BETTER.

Winter will never see it coming, but with the FISHER® Low Profile tailgate spreaders, you'll have a clear view as you take on icy conditions. Perfect for spreading #1 rock salt, calcium chloride and other de-icing materials, these single-stage tailgate spreaders give you visibly better performance in an operator-friendly package.



MODEL 500 | 5.0 cu ft

- Designed for pickups or SUVs with a Class III trailer hitch
- Comes standard with a 2" receiver hitch mount for easy installation on many vehicles
- 10" polyurethane spinner delivers a spreading width of up to 30'
- Nylon ratchet straps come standard for added stability

MODEL 1000 | 8.0 cu ft

- Designed for full size trucks over 6,000 lb GVWR
- Available mount options include a fixed mount, dual swing mount or a Class IV receiver hitch mount. Mounts sold separately
- 10" polyurethane spinner delivers a spreading width of up to 30'

MODEL 2500 | 8.5 cu ft

- Designed for full size trucks over 6,000 lb GVWR
- Comes standard with a Class IV receiver hitch mount for easy attaching/detaching
- 3-flight auger traps material more effectively resulting in less spillage even if feed gates are left open
- A specialized "saw-tooth" feed gate and auger design combine to deliver complete, reliable flow control with positive shut-off, eliminating spillage and waste
- Large, 15" polyurethane spinner delivers a spreading width of up to 30'
- Includes adjustable material deflector for extra control
- Nylon ratchet straps come standard for added stability

UNIVERSAL FEATURES

Covers

A latching, molded poly lid protects material from the elements.

Motors

A fully enclosed 1/3 hp, 12-volt electric motor is mounted inside a sealed housing, protecting it from corrosion.

Controls

Choose between a variable speed control with an "on/off" button and blast option to optimize material usage or a basic "on/off" toggle control (controls are sold separately).

Corrosion-Resistant Hopper

Low profile, corrosion-free poly hoppers for long-lasting performance season after season.

Vertical Steel Auger

Material is delivered by a vertical steel auger. The unique design helps break up clumps and prevents material from spilling.

ACCESSORIES

Model 500, 1000 and 2500
Top Screen | 5 Flight Auger
Adjustable Deflector
Truck Protector Flap (Model 1000 only)

SPEED»CASTER™ 525 & SPEED»CASTER™ 900

THE TRIPLE THREAT.

Delivering speed, control and versatility, the FISHER® SPEED-CASTER™ 525 and SPEED-CASTER™ 900 tailgate spreaders are true triple threats. These spreaders offer a two-stage, auger-fed delivery system with independent control of material flow and spread pattern, so you can deliver exactly the right de-icing material exactly where you want it. And the best part? You don't have to sacrifice any cargo space to do it.



SPEED-CASTER™ 525 SPREADER

Features a 5.25 cu ft poly hopper for long lasting durability that holds up to 420 lbs of bagged or bulk de-icing material.

SPEED-CASTER™ 900 SPREADER

Features a 9.0 cu ft poly hopper for long lasting durability that holds up to 720 lbs of bagged or bulk de-icing material.

Dual Electric Motors

Two high-torque, 12-volt electric motors provide quiet, reliable, independent control over the auger and spinner mechanisms. The spinner motor is sealed inside a weather-resistant housing, protecting it from corrosion.

Dual Variable-Speed Control

Enhanced, dual variable-speed control allows you to precisely match material delivery and spread patterns to conditions. Four standard accessory buttons and a dedicated blast button provide optimum in-cab efficiency. Easy-to-understand, digital self-diagnostics alert the operator when the hopper is empty or when adjustments are needed, and LEDs make the control easy to read. Its compact size compared to traditional controls fits easily into today's modern truck cab designs.

SIZE AND MOUNT OPTIONS

SPEED-CASTER 525 | 5.25 cu ft
Comes standard with a combination 2" receiver hitch and 3-point hitch mount.

SPEED-CASTER 900 | 9.0 cu ft
Available mount options include a pivot mount, a 2" receiver hitch mount (requires additional adapter) and a 3-point hitch mount.*

*Mounts sold separately

Material Delivery

Material is delivered by a heavy-duty, powder coated, horizontal steel auger that automatically backs itself in and out until an obstruction is cleared or a required adjustment has been made.

Spinner and Spreading Width

The SPEED-CASTER 525 spreader features a 10" spinner made of nylon/glass-reinforced resin that delivers a spreading width up to 30'. The SPEED-CASTER 900 spreader features a 12" steel spinner that delivers a spreading width up to 40'.

Inverted V / Vibrator

An inverted V helps keep material weight off the auger, ensuring smooth startup and flow of material. It is directly connected to the vibrator to reduce bridging and keep material moving to the auger.

Accessory Integration

Accessories automatically integrate with the tailgate control without having to run additional wires from the front of the truck.

Top Screen and Lid

The steel-rod top screen breaks up chunks of de-icing material and a molded polyethylene lid protects the material from the elements.

ACCESSORIES

Auger Tube Restrictor Kit | Work Light Kit

QUICK»CASTER™ 300W

MADE FOR CONVENIENCE.

Embrace convenience with the FISHER® QUICK-CASTER™ 300W wireless electric tailgate spreader. It's the ultimate in "plug 'n' play" ice control. With a completely wireless key-fob control, standard 2" receiver hitch and 7-pin connector, it's easy to plug in, load up and get to work.



Photos shown with optional cover accessory



12-Volt Electric Motor

The specially designed, 1/3 hp, 12-volt electric motor and high-torque transmission are fully enclosed for protection from the elements.

Wireless Control

One-touch, on/off operation offers two spinner speeds to match the spread pattern to the job.

Corrosion-Resistant Hopper

The QUICK-CASTER™ 300W wireless electric tailgate spreader features a corrosion-free poly hopper for long-lasting durability.

Material Delivery

Material is delivered by a vertical steel auger. The unique design helps break up clumps and prevents material from spilling.

Spinner and Spreading Width

A 10", corrosion-free spinner delivers a spreading width of up to 25' and ensures optimum delivery of ice melt and long-lasting performance.

Easy On / Easy Off

Attaching and detaching the QUICK-CASTER 300W tailgate spreader is easy with a standard 7-pin plug.

SIZE AND MOUNT OPTIONS

3.0 cu ft

Comes standard with a 2" receiver mount.

Additional mounts available include a drop utility, 3-point, trailer and utility mount.

ACCESSORIES

Clear Weather Cover

Supplemental 7-pin Harness Kit
(for vehicles with no 7-pin trailer hookup)

WB-100B – WB-160D

GROUND ATTACK.

When you have to take a boots-on-the-ground approach to de-icing, the WB-100B and WB-160D are the perfect tools for broadcast-spreading across wider areas or drop-spreading along narrow walkways. These professional walk-behind spreaders are built tough to keep step with you, storm after storm and season after season.



WB-100B Broadcast Spreader

The WB-100B poly broadcast spreader is ideal for broadcast-spreading wider areas such as driveways, courtyards, and wide walkways. 100 lb capacity.

WB-160D Drop-Style Spreader

The WB-160D poly drop-style spreader is perfect for drop-spreading along narrow walkways and keeping material out of adjoining landscape features. 160 lb capacity.

Standard Features

- Clear hopper cover
- 13" pneumatic tires
- Top screen
- Powder coated steel frame

Standard Features for WB-100B Only

- 10" molded spinner
- Nylon-composite gear drive

SS-120

LAY THE GROUNDWORK.

Think of the FISHER® SS-120 walk-behind sprayer as the tool you need to do the work before the work. It holds 12 gallons of liquid anti-icer so you can treat sidewalks and stairs before the storm hits, making snow and ice removal easier. By pretreating, you can use less salt, save time and move on to the next job.



Capacity

12-gallon poly tank with easy-fill cap.

Battery-Powered Electric Pump

12-volt electric pump sprays up to one gallon per minute at 60 psi. Battery powers up to ten full tanks (120 gal) with a single charge.

Rechargeable Battery

Recharges in 12–16 hours.

Height-Adjustable Nozzle

The height-adjustable nozzle sprays up to four feet wide.

Convenient Spray Wand

Use the convenient spray wand with 8' coil hose to treat stairs, entryways and other hard-to-reach places. Features a spray distance of 15'.

Oversize Tires

Large, 13" pneumatic tires enhance maneuverability over ice and snow.



COMPLETE YOUR FLEET

FISHER® Genuine Factory-Tough accessories are manufactured with the FISHER quality you've come to expect. They're designed to enhance your spreader's performance and longevity while also allowing you to customize your spreader to meet the specific demands of each unique account. Consult your local FISHER Dealer or fisherplows.com for more information regarding accessory compatibility and availability.



Pre-Wet System
Pre-wet with a brine solution to melt ice faster and have greater control over your material.
Fits: STEEL-CASTER™ (shown) and POLY-CASTER™



Work Light Kit
For better visibility at rear of spreader at night.
Fits: STEEL-CASTER (shown), POLY-CASTER, SPEED-CASTER™ 525 and SPEED-CASTER™ 900



Strobe Light Kit
For safety during operation.
Fits: STEEL-CASTER (shown) and POLY-CASTER



Vibrator Kit
Helps move stubborn material.
Fits: STEEL-CASTER (shown) and POLY-CASTER



Central Point Grease Kit
Provides easy access to grease points, simplifying preventative maintenance greasing that is essential to maximize bearing life.
Fits: STEEL-CASTER and POLY-CASTER (shown)



Ratchet Tie-Down Kit / Tie-Down Chain Kit
For in-bed stability and security.
Fits: POLY-CASTER (Ratchet Tie-Down Kit - shown) STEEL-CASTER (Tie-Down Chain Kit)



License Plate Kit
To illuminate alternate license plate location.
Fits: STEEL-CASTER and POLY-CASTER (shown)



Spill Guard Kit
Provides loader with improved line of sight and prevents material overflow from off-center loading.
Fits: STEEL-CASTER



6" Side Extensions
Increase the carrying capacity with these 6" tall bolt-on brackets (wood not included).
Fits: STEEL-CASTER



Master Accessory Harness
Integrate accessories into the control with this convenient kit.
Fits: STEEL-CASTER Gas and Hydraulic models



Stainless Steel Inverted V Kit
Helps reduce heavy startup loads on the drivetrain.
Fits: POLY-CASTER



Optimum Flow Kit
Improves material flow and allows spreading of a 50/50 salt/sand mix with a vibrator and dual-pitch baffle.
Fits: POLY-CASTER™ UTV



Auger Tube Restrictor Kit
Helps prevent leaking issues when handling fine pellet and flake materials.
Fits: POLY-CASTER UTV, SPEED-CASTER 525 and SPEED-CASTER 900



Clear Weather Cover
The transparent cover keeps material dry and flowing freely, while offering a clear view inside the hopper.
Fits: QUICK-CASTER™ 300W

MOUNTS & MATERIAL COMPATIBILITY

MOUNTS GUIDE

	LOW PROFILE 500	LOW PROFILE 1000	LOW PROFILE 2500	SPEED-CASTER™ 525	SPEED-CASTER™ 900	QUICK-CASTER™ 300W
TAILGATE SPREADER MOUNTS						
RECEIVER HITCH MOUNT	std	•	std	std	•*	std
FIXED MOUNT		•				
DUAL SWING MOUNT		•				
UTILITY MOUNT						•
DROP UTILITY MOUNT						•
TRAILER MOUNT						•
3-POINT MOUNT				std	•	•
PIVOT MOUNT					•	

std = Included standard with spreader
• = Sold separately
* Requires additional adapter

MATERIALS GUIDE

MATERIAL TYPE	ALL STEEL-CASTER™	ALL POLY-CASTER™	POLY-CASTER™ UTV	LOW PROFILE 500	LOW PROFILE 1000	LOW PROFILE 2500	SPEED-CASTER 525	SPEED-CASTER 900	QUICK-CASTER 300W
	HOPPERS		UTV	TAILGATES					
BAGGED ICE MELTERS	X	X	X*	X	X	X	X*	X*	
BAGGED ROCK SALT	X	X	X	X	X	X	X	X	X
BULK SALT	X	X	X				X	X	
CALCIUM FLAKES	X	X	X*	X†	X†	X†	X*	X*	
CALCIUM CHLORIDE PELLETS	X	X	X*	X†	X†	X†	X*	X*	
50/50 SALT/SAND MIX	X	X	X**				X	X	
SAND	X	X	X**				X	X	

NOTE: Assumes dry, free-flowing materials
*May require use of auger tube restriction kit accessory
**May require use of optimum flow kit accessory
†May require accessory 5 flight auger

MATERIAL TYPE	WB-100B	WB-160D
	WALK-BEHINDS	
BAGGED ICE MELTERS	X	X
BAGGED ROCK SALT	X	X
BULK SALT	X	X
CALCIUM FLAKES	X	X
CALCIUM CHLORIDE PELLETS	X	X
50/50 SALT/SAND MIX		
SAND		

MATERIAL TYPE	SS-120 SPRAYER	PRE-WET SYSTEM
	WALK-BEHIND	ACCESSORY
BRINE	X	X
CALCIUM CHLORIDE SOLUTION	X	X
PREMIUM SOLUTIONS	X	X

Selecting the proper de-icing materials can vary by operator preference, experience and environmental considerations. Consult your local FISHER dealer with questions regarding material selection and availability.

SPECIFICATIONS

STEEL-CASTER™



SPREADER TYPE	HOPPER	HOPPER	HOPPER	HOPPER	HOPPER	HOPPER
BODY SIDE LENGTH	7' (2.13 m)	8' (2.44 m)	9' (2.74 m)	9' (2.74 m)	10' (3.05 m)	10' (3.05 m)
CAPACITY	1.50 cu yd (1.15 cu m)	2.00 cu yd (1.53 cu m)	3.00 cu yd (2.29 cu m)	4.50 cu yd (3.44 cu m)	4.50 cu yd (3.44 cu m)	6.00 cu yd (4.59 cu m)
HOPPER CONSTRUCTION	16 ga SS (1.50 mm)	16 ga SS (1.50 mm)	16 ga SS (1.50 mm)	16 ga SS (1.50 mm)	16 ga SS (1.50 mm)	16 ga SS (1.50 mm)
DIMENSIONS OVERALL	84" x 50" x 38" (214.00 cm x 127.00 cm x 97.00 cm)	96" x 50" x 33" (244.00 cm x 127.00 cm x 84.00 cm)	108" x 50" x 41" (275.00 cm x 127.00 cm x 105.00 cm)	108" x 70" x 47" (275.00 cm x 178.00 cm x 120.00 cm)	120" x 70" x 47" (305.00 cm x 178.00 cm x 120.00 cm)	120" x 70" x 54" (305.00 cm x 178.00 cm x 138.00 cm)
DUAL 12V DC SEALED MOTORS	595 lb (269.89 kg)	615 lb (278.96 kg)	695 lb (315.25 kg)	815 lb (369.68 kg)	—	—
GAS 10.5 hp I/C BRIGGS & STRATTON®	—	740 lb (335.66 kg)	820 lb (371.95 kg)	940 lb (426.38 kg)	965 lb (437.72 kg)	1010 lb (458.13 kg)
GAS 11 hp I/C HONDA®	—	740 lb (335.66 kg)	820 lb (371.95 kg)	940 lb (426.38 kg)	965 lb (437.72 kg)	1010 lb (458.13 kg)
DUAL HYDRAULIC MOTORS	—	615 lb (278.96 kg)	695 lb (315.25 kg)	815 lb (369.68 kg)	840 lb (381.02 kg)	885 lb (401.43 kg)
CONVEYOR WIDTH	16 1/2" (42.00 cm)	16 1/2" (42.00 cm)	16 1/2" (42.00 cm)	16 1/2" (42.00 cm)	16 1/2" (42.00 cm)	16 1/2" (42.00 cm)
SPINNER SIZE	15 1/2" (40.00 cm)	15 1/2" (40.00 cm)	15 1/2" (40.00 cm)	15 1/2" (40.00 cm)	15 1/2" (40.00 cm)	15 1/2" (40.00 cm)
SPREADING WIDTH	Up to 40' (12.19 m)	Up to 40' (12.19 m)	Up to 40' (12.19 m)	Up to 40' (12.19 m)	Up to 40' (12.19 m)	Up to 40' (12.19 m)
MATERIALS	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix
VEHICLE APPLICATION	3/4- & 1-Ton Pickup Trucks	3/4- & 1-Ton Pickup Trucks	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)

POLY-CASTER™



SPREADER TYPE	HOPPER	HOPPER	HOPPER
BODY SIDE LENGTH	7' (2.13 m)	8' (2.44 m)	8' (2.44 m)
CAPACITY	1.50 cu yd (1.15 cu m)	1.80 cu yd (1.38 cu m)	2.50 cu yd (1.91 cu m)
HOPPER CONSTRUCTION	Polyethylene	Polyethylene	Polyethylene
DIMENSIONS OVERALL	108" x 63" x 44" (274.00 cm x 160.00 cm x 112.00 cm)	117" x 63" x 44" (297.00 cm x 160.00 cm x 112.00 cm)	117" x 63" x 51" (297.00 cm x 160.00 cm x 130.00 cm)
APPROX. WEIGHT (EMPTY)	591 lb (268.07 kg)	660 lb (299.37 kg)	734 lb (332.94 kg)
MOTORS	Dual Electric, 12V, Sealed	Dual Electric, 12V, Sealed	Dual Electric, 12V, Sealed
CONVEYOR WIDTH	16 1/2" (42.00 cm)	16 1/2" (42.00 cm)	16 1/2" (42.00 cm)
SPINNER SIZE	15 1/2" (40.00 cm)	15 1/2" (40.00 cm)	15 1/2" (40.00 cm)
SPREADING WIDTH	Up to 40' (12.19 m)	Up to 40' (12.19 m)	Up to 40' (12.19 m)
MATERIALS	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix
VEHICLE APPLICATION	3/4- & 1-Ton Pickup Trucks	3/4- & 1-Ton Pickup Trucks	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)



LOW PROFILE

SPREADER TYPE	TAILGATE	TAILGATE	TAILGATE	TAILGATE	TAILGATE	TAILGATE
MODEL	500	1000	2500	525	900	300W
CAPACITY	5.00 cu ft (0.14 cu m)	8.00 cu ft (0.23 cu m)	8.50 cu ft (0.24 cu m)	5.25 cu ft (0.15 cu m)	9.00 cu ft (0.25 cu m)	3.00 cu ft (0.09 cu m)
HOPPER CONSTRUCTION	Polyethylene	Polyethylene	Polyethylene	Polyethylene	Polyethylene	Polyethylene
DIMENSIONS OVERALL	21" x 39" x 34" (53.34 cm x 99.06 cm x 86.40 cm)	19 1/2" x 50 1/2" x 35" (49.53 cm x 128.27 cm x 88.90 cm)	25" x 50" x 42" (63.50 cm x 127.00 cm x 106.68 cm)	20 1/2" x 38" x 34" (52.10 cm x 96.50 cm x 86.40 cm)	24" x 52" x 36" (60.90 cm x 132.10 cm x 91.40 cm)	22" x 30" x 32" (55.90 cm x 76.20 cm x 81.30 cm)
APPROX. WEIGHT (EMPTY)	75 lb with mount (34.00 kg)	105 lb w/o mount* (47.00 kg)	131 lb with mount (59.40 kg)	160 lb with mount (72.60 kg)	180 lb w/o mount* (81.70 kg)	68 lb with mount (30.80 kg)
MOTOR	Electric, 12V 1/8 hp	Electric, 12V 1/8 hp	Electric, 12V 1/8 hp	Dual Electric, 12V 1/8 hp	Dual Electric, 12V 1/8 hp	Electric, 12V 1/8 hp
AUGER (DIA. x LENGTH)	2.63" x 6" (6.68 cm x 15.24 cm)	2.63" x 6" (6.68 cm x 15.24 cm)	2.63" x 9" (6.68 cm x 22.86 cm)	3" x 14" Heavy-Duty Solid Steel (7.26 cm x 35.56 cm)	3" x 20" Heavy-Duty Solid Steel (7.26 cm x 50.80 cm)	2 1/2" x 5 3/4" Vertical High-Flow (6.35 cm x 14.61 cm)
SPINNER SIZE	10" (25.40 cm)	10" (25.40 cm)	15" (38.10 cm)	10" (25.40 cm)	12" (30.50 cm)	10" (25.40 cm)
SPREADING WIDTH	Up to 30' (9.14 m)	Up to 30' (9.14 m)	Up to 30' (9.14 m)	Up to 30' (9.14 m)	Up to 40' (12.19 m)	Up to 25' (7.62 m)
MATERIALS	Salt	Salt	Salt	Bagged Rock Salt, Dry Free-Flowing Sand, 50/50 Salt/Sand Mix	Bagged Rock Salt, Dry Free-Flowing Sand, 50/50 Salt/Sand Mix	Salt
VEHICLE APPLICATION	Vehicles with Class III Hitch	Full Size Trucks (over 6,000 lb GVWR)	Full Size Trucks (over 6,000 lb GVWR)	Tractors, SUVs, 1-Ton or Smaller Pickups	Tractors, SUVs, 1-Ton or Smaller Pickups	Tractors, UTVs, SUVs, 1-Ton or Smaller Pickups
AVAILABLE MOUNTS	Standard Class III Hitch Receiver Mount	Optional Fixed Mount, Class IV Hitch Mount, Dual Swing Mount	Standard Class IV Hitch Mount	Standard 2" Receiver, 3-Point Combo Mount	Pivot Mount, 2" Receiver Mount (requires adapter mount), 3-Point Hitch Mount	Standard 2" Receiver, Trailer Utility, 3-Point Mounts*

*Mounts sold separately



POLY-CASTER™ UTV

SPREADER TYPE	UTV	WALK-BEHIND	WALK-BEHIND
BODY SIDE LENGTH	64" (1.63 m)	—	—
CAPACITY	11.00 cu ft (0.31 cu m)	160 lb (72.00 kg)	100 lb (45.00 kg)
HOPPER CONSTRUCTION	Polyethylene	Polyethylene	Polyethylene
DIMENSIONS OVERALL	64" x 48 1/2" x 27" (163.00 cm x 123.00 cm x 69.00 cm)	48" x 38 1/4" x 36" (121.92 cm x 97.16 cm x 91.44 cm)	50" x 26" x 28" (127.00 cm x 66.04 cm x 71.12 cm)
APPROX. WEIGHT (EMPTY)	280 lb (127 kg)	55 lb (24 kg)	25 lb (11 kg)
MOTORS	Dual Electric, 12V DC, Sealed	—	—
SPINNER SIZE	12" (30.00 cm)	—	10" (25.40 cm)
SPREADING WIDTH	Up to 30' (9.14 m)	3' (0.91 m)	Up to 20' (6.00 m)
MATERIALS	Salt or 50/50 Salt/Sand Mix	Bagged Ice Melters & Bagged Rock Salt	Bagged Ice Melters & Bagged Rock Salt
VEHICLE APPL.	UTVs	—	—



WB-160D WB-100B



SPRAYER

SPREADER TYPE	WALK-BEHIND
MODEL	SS-120
EMPTY WEIGHT	60 lb (27.20 kg)
DIMENSIONS OVERALL	48" x 28" x 33" (122.00 cm x 71.00 cm x 84.00 cm)
CAPACITY	12 gal (45.40 L)
SPRAYING WIDTH	Up to 48" (122.00 cm)
SPRAYING VOLUME	1 gal/min (3.80 L/min)
FRAME	Powder Coated Steel
TANK	One-Piece LLDPE Safety Yellow
MOTORS	Direct-Drive Pump

Photos may be shown with optional accessories.

Specifications subject to change without prior notice. Please visit fisherplows.com for the most accurate specifications.



Fisher Engineering | 50 Gordon Drive | Rockland, Maine 04841

fisherplows.com



Fisher Engineering reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Fisher Engineering or the vehicle manufacturer may require or recommend optional equipment for spreaders. Do not exceed vehicle ratings with a spreader. This product is manufactured under the following US patents: 5,638,618; 5,899,007; 6,253,470; 6,408,549; 6,944,978; 7,400,058; 7,430,821; 7,681,334; 7,737,576; 7,797,859; CAN patents 2,184,922; 2,229,783; 2,356,036 and other patents pending. Fisher Engineering offers a limited warranty on all spreaders and accessories. See separately printed page for this important information. The following are registered(®) and unregistered(™) trademarks of Douglas Dynamics, LLC: FISHER®, Fish-Stik®, HD2™, HDX™, HT Series™, INTENSIFIRE™, Minute Mount®, Minute Mount® 2, POLY-CASTER™, POLY-CASTER™ UTV, QUICK-CASTER™ 300W, SECURITY GUARD™, SnoFoil®, SPEED-CASTER™ 525 & 900, STEEL-CASTER™, STORM BOXX™, STORM GUARD™, TRAILBLAZER™, XLS™, XtremeV™ and XV2™.

© 2018 Douglas Dynamics, LLC
All rights reserved.

A DIVISION OF FISHER, LLC

Printed in U.S.A.
Form No. 77025 — AU18