

# Equipment Hauler Angle Frame



\*Shown with optional Wood Ramps, 12K Jack, Spare Tire & Wheel, and Spare Tire Mount



Scan for  
more info!



[WWW.CAMSUPERLINE.COM](http://WWW.CAMSUPERLINE.COM)

# Equipment Hauler Angle Frame

## STANDARD FEATURES

- Dexter EZ Lube Axles (4" Drop) (Oil Bath on 8 Ton)
- Nev-R-Adjust Brakes (N/A on 8 Ton)
- Slipper-Spring Suspension
- Electric Brakes (2) Axles
- 5' Quick Release Ramps (Angle or Wood Filled)
- Diamond Plate Fenders
- 7K Bolt-on Drop Leg Jack (12K on 8 Ton)
- LED Lights – Rubber Mounted
- Adjustable 2-5/16" Ball Coupler or Pintle
- D-Ring Tie-Downs – 5/8" (6)
- Stake Pockets (8)
- Aluminum Tool Box
- P/T Pine Decking (Oak on 8 Ton)
- Silver Wheels
- Solar Charged Breakaway
- Sealed Wiring Harness
- 7-Way RV Plug
- Safety Chains
- Epoxy Primer
- Polyurethane Paint Finish
- Colors (standard): Black, Yellow
- **Two Year Warranty**

## SPECIFICATIONS

Model#	5CAM18	6CAM18	7CAM18	8CAM18
GVWR:	11,960 lbs.	13,800 lbs.	16,100 lbs.	18,400 lbs.
Empty Weight:	2,300 lbs.	2,960 lbs.	3,200 lbs.	3,810 lbs.
Payload:	9,660 lbs.	10,840 lbs.	12,900 lbs.	14,590 lbs.
Deck Length:	18'	18'	18'	18'
Overall Width:	102"	102"	102"	102"
Usable Deck Width:	82.5"	81"	81"	81"
Deck Height:	20"	21"	21"	22"
Axle Capacity:	5,080 lbs.	6,000 lbs.	7,000 lbs.	8,000 lbs.
Radial Tire Size:	225/75R15LRD	235/80R16LRE	235/80R16LRE	215/75R17.5LRH
Main Frame:	6"x4"x 5/16" Angle	6"x4"x5/16" Angle	6"x4"x3/8" Angle	6"x4"x1/2" Angle
Crossmembers:	3" Channel @ 4.1#	3" Channel @ 4.1#	3" Channel @ 4.1#	3" Channel @ 4.1#
Tongue:	6" Channel @ 8.2#	6" Channel @ 8.2#	6" Channel @ 10.5#	6" Channel @ 10.5#

## OPTIONS AVAILABLE

- Extra Deck Length (20', 22', 24')
- 5' Spring Assisted Split Landscape Ramp
- Landscape Rail (2" x 1 1/2" x 1/8")
- Winch Mount
- Spare Tire and Wheel
- Spare Tire Mount
- 12K Bolt-on Drop Leg Jack (Standard on 8 Ton)
- Oak Deck (Standard on 8 Ton)
- 3/16" Diamond Plate Decking
- Stake Pockets & Rub Rail
- Torflex Axles (Not Available on 8 Ton)
- Pallet Fork Carrier (N/A w/Gooseneck)
- Goodyear Tires
- Gooseneck with Adjustable Coupler, Tool Box and Dual 12K Jacks
- Forklift Tread Package
- Aluminum Wheels
- Additional D-Ring Tie Downs – 5/8"
- Mud Flaps
- Springs on Ramps (Standard on 8 Ton)
- Custom Colors
- Galvanizing
- Galvanized Wheels
- Optional Colors: Red, Gray, Orange, Blue, Green



5' Split Landscape Ramps (optional)



Pallet Fork Carrier



Tongue Area



Specifications  
subject to change  
without notice.

10-16 Printed in the USA



**Quality. Service. Value. Dependability.**

4763 Zane Miller Drive  
Waynesboro, PA 17268

Toll Free: 800.378.7623  
Fax: 800.279.7578

[www.camsuperline.com](http://www.camsuperline.com)

