

Heavy Duty Deckover 10, 12, 15 Ton Models



Scan for
more info!



WWW.CAMSUPERLINE.COM

Heavy Duty Deckover 10, 12, 15 Ton Models

STANDARD FEATURES

- Steel Plated Tongue
- Dexter Oil Bath Axles
- Adjustable Slipper Spring Suspension
- Hi-Tensile Steel Construction
- Full Pierced Beam Construction
- Dual 12K 2-Speed Jacks (Bolt-on) - Dual 50k on 15 Ton
- 5' Bi-Directional Spring Assisted Wood Filled Ramps
- Nominal 2" Oak Deck
- Silver Wheels
- LED Lights – Rubber Mounted
- Adjustable Pintle Hitch
- Tool Box
- D-Ring Tie Downs (12) – 3/4"
- Mud Flaps
- Steps (4)
- Solar Charged Breakaway (Electric Brake Units)
- 7-Way RV Plug (Electric)
- 7-Way Pin Plug (Air)
- Sealed Wiring Harness
- Safety Chains (1/2" High Test)
- Epoxy Primer
- Polyurethane Paint Finish
- Colors (standard): Black, Yellow
- **Two Year Warranty**



Tongue Area w/Step



Self Clean Beavertail & Ramps (optional)

SPECIFICATIONS

Model#	10CAM825TE	10CAM825TA	12CAM825TE	12CAM825TA	15CAM825TE
GVWR:	26,450 lbs.	26,525 lbs.	30,650 lbs.	30,725 lbs.	37,500 lbs.
Empty Weight:	6,450 lbs.	6,525 lbs.	6,650 lbs.	6,725 lbs.	7,500 lbs.
Payload:	20,000 lbs.	20,000 lbs.	24,000 lbs.	24,000 lbs.	30,000 lbs.
Deck Length:	25' (20' Flat, 5' B/T)	25' (20' Flat, 5' B/T)	25' (20' Flat, 5' B/T)	25' (20' Flat, 5' B/T)	25' (20' Flat, 5' B/T)
Overall Width:	102"	102"	102"	102"	102"
Deck Height:	34"	34"	34"	34"	35"
Axle Capacity:	10,000 lbs.	10,000 lbs.	12,000 lbs.	12,000 lbs.	15,000 lbs.
Radial Tire Size:	235/80R16LRE Dual	235/80R16LRE Dual	235/80R16LRE Dual	235/80R16LRE Dual	215/75R17.5LRH Dual
Main Frame & Tongue:	12" I-Beam @ 16#	12" I-Beam @ 16#	12" I-Beam @ 16#	12" I-Beam @ 16#	12" I-Beam @ 22#
Crossmembers:	3" Channel @ 4.1#	3" Channel @ 4.1#	3" Channel @ 4.1#	3" Channel @ 4.1#	3" Channel @ 4.1#
Brakes:	Electric	Air w/ABS	Electric	Air w/ABS	Electric

OPTIONS AVAILABLE

- Extra Deck Length (32' Max)
- Gooseneck with Adjustable Coupler or King Pin and Dual 12K 2-Speed Jacks (30' Deck Max)
- Upper Deck Platform for Gooseneck
- Self Cleaning Beavertail and Ramps
- Double Break Beavertail (7.5') with 6' Ramps
- 30" x 80" Air Power Ramps (Air Brake Models Only) (Requires 102" Width, 27' Minimum Length)
- 40" x 80" Air Power Ramps (Air Brake Models Only) (Requires 102" Width, 27' Minimum Length)
- 40" x 80" Hydraulic Power Ramps (Requires 27' Minimum Length)
- 36" Knife-Edge Paver Extensions (40" x 80" Air Ramps Only)
- Wide-Track Axles
- Winch Mount
- 6' Angle/Wood Ramps
- Aluminum Wheels
- Underbody Tool Box (14"x16"x36")
- Spare Tire & Wheel
- Spare Tire Carrier (Under Bed)
- Stake Pockets & Rub Rail (102" Outside Rail Dimension)
- Additional D-Ring Tie-Downs – 3/4"
- Custom Colors
- Galvanizing
- Optional Colors: Red, Gray, Orange, Blue, Green



Gooseneck with Upper Deck Platform (optional)



Specifications
subject to change
without notice.



10-16 Printed in the USA



Quality. Service. Value. Dependability.

4763 Zane Miller Drive
Waynesboro, PA 17268

Toll Free: 800.378.7623
Fax: 800.279.7578

www.camsuperline.com