

MUNICIPAL DUMP SPREADER (MDS)

Dual 7 Inch Auger or 30-1/2 Inch Conveyor Chain Feed



HIGHLIGHTS



Unique, roll-formed sides and cross member-less design



"Hex flow" chute and 24 inch spinner with adjustable baffles for optimal spread pattern



Mailhot® multi-stage, double-acting, nitrided cylinder, trunnion-mounted hoist



Dual air tailgate cylinders standard

AVAILABLE OPTIONS



Cab shield with Built-In Tarp System

- Cab Shield: Half or Full Length with Optional Built in Tarp Housing
- Ladder
- Top Screens
- Electric Tarp

- Under Chain Floor Pan
- Anti-Ice
- Central Hydraulics
- Full Length Fenders
- Pre-Wet Systems: (LS11, LS11H, LS12, LS12H)



30.25" wide conveyor with 1/2" bars



Dual 7" auger drive

OR



Ladder shown extended down



LS11 (MDS Mount two, 160 gal.)



LS12 (Behind Cab Mount 120 gal.)

COMMON FEATURES

Capacity: 6.4 - 11.2 cubic yards /9 - 15 feet/ (see pg. 51)

Application: Minimum 26,000 lb GVW

Spread Range: 2-40 feet

Feed Mechanism: 30-1/2 inch wide conveyor with 1/2 inch crossbars every link or dual 7 inch auger drive

Construction: 304 stainless steel body construction

- Additional Features:**
- Removable conveyor cover plate
 - Twin air cylinder tailgate latch
 - LED DOT truck lights and rear strobes