

ALX ALUMINUM MOTORCYCLE TRAILERS

| | | HAMV75X12WT2 | HAMV75X14WT2 | HAMV75X16WT2 |
|---------------------------|------------------------|---|---|---|
| Body: | Length (including "V") | 14′11″ | 16′5″ | 18′5″ |
| | Width | 7'6" | 7'6" | 7′6″ |
| Overall: | Length | 17′2″ | 18'8" | 20'8" |
| | Width | 8'6" | 8'6" | 8'6" |
| | Height | 6'11" | 6'11" | 6'11" |
| Interior: | Length (including "V") | 14'6" | 16′1″ | 18'1" |
| | Length (without "V") | 12′3″ | 13′9″ | 15'9" |
| | Width | 7′3″ | 7′3″ | 7′3″ |
| | Height | 5′3″ | 5′3″ | 5′3″ |
| Platform Height: | | 13" | 13" | 13" |
| Width Between Wheel Boxes | | 81" | 81" | 81" |
| Axle: | Quantity | Tandem | Tandem | Tandem |
| | Capacity | 7000 lbs. | 7000 lbs. | 7000 lbs. |
| | Туре | 22.5° Up | 22.5° Up | 22.5° Up |
| | Suspension | Dexter Torflex® | Dexter Torflex® | Dexter Torflex® |
| | Brakes | STD | STD | STD |
| Tires: | Size | ST205/75R15 | ST205/75R15 | ST205/75R15 |
| | Load Range | С | С | С |
| | Туре | Radial | Radial | Radial |
| Hitch: | Ball Size | 2 ⁵ / ₁₆ " | 2 5/16" | 2 ⁵ / ₁₆ " |
| | To Top of Ball | 17" | 17" | 17" |
| GVWR | | 7000 lbs. | 7000 lbs. | 7000 lbs. |
| Rear Door: W x H | | 81 ³ / ₄ " x 62 ¹ / ₂ " | 81 ³ / ₄ " x 62 ¹ / ₂ " | 81 ³ / ₄ " x 62 ¹ / ₂ " |
| Side Door: W x H | | 32" x 54" | 32" x 54" | 32" x 54" |
| 12V End Connector: | | 7-way | 7-way | 7-way |



- All-Aluminum Hardware
- Aluminum Tube Perimeter Frame
- Fully Integrated, All Tube, Roof and Sidewall Design
 - 24" OC Floor Crossmembers
 - 16" OC Wall Posts
 - 24" OC Roof Framing
- V-Nose Front with Slope
- Low Profile Design for Easy Loading/Unloading
- 18" Beavertail
- Drop-Down Cornerpost Jacks
- Silver Aluminum Wheels
- Rubber RTP Flooring, Ramp Deck and Extension
- White Vinyl Sidewalls & Ceiling
- ABS Sidewall Vents (pr.)
- Removable Wheel Chocks (2)
- 5000# D-Rings (8)
- Aluminum Transition Flap Over Hinge
- LED Dome Light with Switch (Made in the USA)

- .030 Bonded (Screwless) Exterior
- Wide Extruded Aluminum Top/Bottom Trim for Bold Appearance
- Innovative "Overlock" Aluminum Roof Design is Screwless and Seamless
- 32" Aluminum Framed Side Door with Flush Lock
- Spring-Assisted Rear Ramp Door with 16" Flap (3000# rated)
- Aluminum Bar Locks on Rear Door
- 24" ATP Stoneguard
- LED Exterior Lighting Tail/Clearance (Made in the USA)
- **■** 6-Year Limited Warranty

Popular Options

- **■** Extruded Aluminum Floor
- .030 Screwless Aluminum Interior Wall Liner



All Aluminum Design



Striking Interior Shown with standard Rubber RTP Flooring



Overlock Roof Design — Screwless and Seamless



Aluminum Transition Flap



Cast Aluminum Door Hold Backs



GET MORE | **GO FURTHER**

www.haulmark.com