

Haulmark®

SMART VALUE

BRING YOUR WORLD WITH YOU!

The Passport® is your ticket to carefree and reliable cargo hauling that's easy on your wallet. It's a perfect fit for recreational and light duty applications. Although classified as an "entry level" trailer, the Passport® is loaded with quality features found on much more expensive trailers — features like tubular steel main rails, radial tires, 3/4" PlexCore™ high performance interior flooring, LED exterior lighting and 16" Starbright Stoneguard. The standard V-Nose is not only stylish, but improves handling and MPG. No matter your hauling needs . . . count on the Passport® to deliver your valuables safe and secure to your final destination.



Trailers shown may feature optional equipment available at an additional charge.

Passport®
by Haulmark

SPECIFICATIONS



	PP58S2	PP610S2	PP612S2	PP714T2	PP716T2
Body: Length Width	9' 5" 5' 0"	11' 7" 6' 0"	13' 7" 6' 0"	15' 7" 7' 0"	17' 7" 7' 0"
Overall: Length Width Height	11' 6" 6' 8" 7' 2"	14' 0" 7' 8" 7' 8"	16' 0" 7' 8" 7' 8"	17' 8" 8' 6" 7' 9"	19' 8" 8' 6" 7' 9"
Interior: Length Width Height	9' 1" 4' 8" 5' 6"	11' 3" 5' 8" 6' 0**	13' 3" 5' 8" 6' 0**	15' 3" 6' 8" 6' 0**	17' 3" 6' 8" 6' 0**
Platform Height	18"	18"	18"	19"	19"
Spring Suspension E-Z Lube® Axles: Qty Total Capacity	Single 3,500 lbs.	Single 3,500 lbs.	Single 3,500 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.
Brakes with Breakaway Kit	N/A	Opt.	Opt.	Electric Drum	Electric Drum
Radial Tire Size Tire Load Range	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C
Hitch Ball Size	2"	2"	2"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	16"	16"	16"	17"	17"
Hitch Weight (% of Curb Weight)	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%
Curb Weight (Approximate)	935 lbs.	1,195 lbs.	1,325 lbs.	2,125 lbs.	2,275 lbs.
GVWR	2,980 lbs.	2,980 lbs.	2,980 lbs.	7,000 lbs.	7,000 lbs.
Payload Capacity (Approximate)	2,045 lbs.	1,785 lbs.	1,655 lbs.	4,875 lbs.	4,725 lbs.
Rear Door Opening - Width x Height	51" x 59.25"	63" x 67"	63" x 67"	75" x 67"	75" x 67"
12V Male Connection	4-way	4-way	4-way	7-way	7-way

*6'6" Interior Height on Trailers built in the Waco, TX & Ogden, UT facilities.

STANDARD FEATURES

- Flat Roof/V-Nose Profile
- 15" Radial Tires with Silver Mod Wheels
- Smooth Aluminum Radius Fenders
- Safety Chains with Clevis Hook and Latch
- White .024 Aluminum Exterior (with screws)
- 1-Piece Aluminum Roof
- 12v LED Exterior Lighting
- LED Slim Line Tail Lights
- 16" Starbright Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist (Single Swing Door on 5x8 Model)
- 32" Side Door with Bar Lock (No Side Door on 5x8 Model)
- 12v Dome Light
- 3/4" PlexCore™ Flooring
- Economy Sidewall Liner
- Spring Axles with 4" Drop
- E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit (Tandem Axle Models Only)
- 2" X 4" Tube Main Rails (2" x 3" on Single Axle Models)
- Entire Chassis Undercoated
- 16" OC Vertical Posts
- 24" OC Crossmembers
- 24" OC Tube Roof Bows
- 1-Year Limited Warranty



GET MORE | GO FURTHER

www.haulmark.com

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Haulmark dealer for more information.