

## **SPECIFICATIONS**

## TRANSPORT'

	TS8516T2	TS8520T2	TS8524T2	TS8528T3
Body: Length Width	16' 9" 8' 4"	20' 9" 8' 4"	24' 9" 8' 4"	28' 10" 8' 4"
Length Overall: Width Height	19' 6" 8' 6" 8' 7"	23' 6" 8' 6" 8' 7"	27' 6" 8' 6" 8' 7"	31' 10" 8' 6" 8' 8"
Length Interior: Width Height	16' 5" 8' 0" 6' 7"	20' 5" 8' 0" 6' 7"	24' 5" 8' 0" 6' 7"	28' 6" 8' 0" 6' 8"
Width Between Wheel Boxes	84"	84"	84"	84"
Platform Height at Beavertail	17"	17"	17"	18"
Spring Suspension E-Z <sup>*</sup> Lube Axles: Qty Total Capacity	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 10,200 lbs.
Electric Brakes with Breakaway Kit	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size Tire Load Range	ST205/R15 C	ST205/R15 C	ST205/R15 C	ST225/R15 D
Hitch Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	20"	20"	20"	21"
Hitch Weight (% of Curb Weight)	10% to 15%	10% to 15%	10% to 15%	10% to 15%
Curb Weight (Approximate)	2,805 lbs.	3,245 lbs.	3,685 lbs.	4170 lbs.
<b>GVWR</b>	7,000 lbs.	7,000 lbs.	7,000 lbs.	9,990 lbs.
Payload Capacity (Approximate)	4,195 lbs.	3,755 lbs.	3,315 lbs.	5820 lbs.
Rear Ramp Door Opening - Width x Height	94" X 75"	94" X 75"	94" X 75"	94" X 75"
22V Male Connection	7-way	7-way	7-way	7-way
Beavertail	32"	48"	48"	72"

## STANDARD FEATURES

- · Radius Front/Round Roof with TPO Front Cap
- Spring Axles with E-Z Lube® Hubs
- · Electric Brakes with Breakaway Kit
- Silver Mod Wheels with 15" Radial Tires
- Smooth Aluminum Fenderettes
- 24" ATP Stoneguard
- .030 Aluminum Exterior Bonded (No Screws)
- .080 Aluminum Top Wrap
- 1-Piece Aluminum Roof
- LED Slim Line Tail Lights
- · LED Mini Clearance Lights
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist
- 16" Ramp Extension
- 36" Side Entry Door with Flush Lock
- · Recessed Step at Side Door
- 12V LED Dome Light with Wall Switch (2)
- 3/4" PlexCore<sup>™</sup> Decking
- 3/8" PlexCore™ Sidewall Liner
- 5,000 lb. Square D-Rings with Welded Plate (4)
- Entire Chassis Undercoated
- ArmorTech™ on A-Frame and Rear End Rail
- Tube Main Rails
- 16" OC Tube Vertical Posts
- 16" OC Crossmembers
- 16" OC Roof Bows
- 3-Year Limited Warranty





Trailers shown feature <u>optional</u> equipment available at additional cost.



