

Haulmark®

ENHANCED VALUE

RUGGED, AFFORDABLE AND STYLISH!

Your expectations are simple. Your trailer has to be built solid — durable and dependable for years to come. Your trailer has to be the appropriate size, proper capacity, equipped with the right features and competitively priced. You don't want the cheapest trailer, but you do want the best value for your dollar. At Haulmark®, we build trailers that work as hard as you do.



Trailers shown may feature optional equipment available at an additional charge.

TRANSPORT®

SPECIFICATIONS



		TSV8516T2	TSV8520T2	TSV8524T2	TSV8528T3
Body:	Length	17' 10"	21' 10"	25' 10"	29' 10"
	Width	8' 4"	8' 4"	8' 4"	8' 4"
Overall:	Length	19' 6"	23' 6"	27' 6"	31' 6"
	Width	8' 6"	8' 6"	8' 6"	8' 6"
	Height	8' 7"	8' 7"	8' 7"	8' 8"
Interior:	Length (Includes "V")	17' 6"	21' 6"	25' 6"	29' 6"
	Width	8' 0"	8' 0"	8' 0"	8' 0"
	Height	6' 6"	6' 6"	6' 6"	6' 6"
Platform Height at Beavertail		17"	17"	17"	18"
Spring Suspension E-Z Lube Axles: Qty Total Capacity		Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 10,200 lbs.
Brakes with Breakaway Kit		Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size		ST205/R15	ST205/R15	ST205/R15	ST225/R15
Tire Load Range		C	C	C	D
Hitch Ball Size		2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball		20"	20"	20"	21"
Hitch Weight (% of Curb Weight)		10% to 15%	10% to 15%	10% to 15%	10% to 15%
Curb Weight (Approximate)		2,580 lbs.	3,220 lbs.	3,860 lbs.	4,680 lbs.
GVWR		7,000 lbs.	7,000 lbs.	7,000 lbs.	9,990 lbs.
Payload Capacity (Approximate)		4,420 lbs.	3,780 lbs.	3,140 lbs.	5,310
Rear Ramp Door Opening - Width x Height		94" X 75"	94" X 75"	94" X 75"	94" X 75"
12V Male Connection		7-way	7-way	7-way	7-way
Beavertail		32"	48"	48"	48"

STANDARD FEATURES

- V-Nose/Flat Roof Profile
- Silver Mod Wheels with 15" Radial Tires
- Smooth Aluminum Fenderettes
- .030 Aluminum Exterior Bonded (*No Screws*)
- .080 Aluminum Top Wrap
- 1-Piece Aluminum Roof
- LED Slim Line Tail Lights
- LED Mini Clearance Lights
- 24" ATP Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist
- 16" Ramp Extension
- 36" Side Entry Door with Flush Lock
- Recessed Step at Side Door
- 12v LED Dome Lights with Wall Switch
- 3/4" PlexCore™ Decking
- 3/8" PlexCore™ Sidewall Liner
- 5,000 lb. Square D-Rings with Welded Plate (4)
- Spring Axles with E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit
- Tube Main Rails
- Entire Chassis Undercoated
- ArmorTech™ on A-Frame and Rear End Rail
- 16" OC Tube Vertical Posts
- 16" OC Crossmembers
- 16" OC Tube Roof Bows
- 3-Year Limited Warranty



Trailers shown feature optional equipment available at additional cost.



GET MORE | GO FURTHER

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Haulmark dealer for more information.