

## SPECIFICATIONS Passp@r PP8520T2 PP8524T2 PP8516T2 Length Width 17' 10" 21' 10" 25' 10" 8' 4" 8' 4" 8' 4" Length Width 19'6" 23'6" 27' 6" Overall: 8' 6' 8'6" 8' 6" Height 8'5" 8' 5' 8' 5" 17' 6" 25' 6" Length 21'6' Width 8'0" 8' 0" 8' 0" Height 6'6" 6' 6" 6' 6" 83.5" 83.5" Width Between Wheel Wells 83.5" **Platform Height** 19" 19" 19" Spring Suspension E-Z Lube® Axles: Qty Tandem Tandem Tandem Total Capacity 7,000 lbs. 7,000 lbs. 7,000 lbs. Electric Brakes with Breakaway Kit Electric Drum Electric Drum Electric Drum Radial Tire Size Tire Load Range ST205/75R15 ST205/75R15 ST205/75R15 Hitch Ball Size 2-5/16" 2-5/16" 2-5/16" Hitch Height to Top of Ball 20" 20" 20" Hitch Weight (% of Curb Weight) 10% to 15% 10% to 15% 10% to 15% Curb Weight (Approximate) 2,800 lbs. 3,100 lbs. 3,500 lbs. 7,000 lbs. 7,000 lbs. 7,000 lbs. Payload Capacity (Approximate) 4,200 lbs. 3,900 lbs. 3,500 lbs. 91" x 75" 91" x 75" Rear Ramp Door Opening - Width x Height 91" x 75" 12v Male Connection 7-way 7-way 7-way

## STANDARD FEATURES

- · V-Nose Profile
- 15" Radial Tires with Silver Mod Wheels
- · Smooth Aluminum Fenderettes
- White .024 Aluminum Exterior (with screws)
- 1-Piece Aluminum Roof
- 12v LED Exterior Lighting
- 12v LED Slim Line Tail Lights
- 16" Starbright Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist
- 32" Side Door with Bar Lock
- 12v LED Dome Light
- 3/4" PlexCore<sup>™</sup> Decking
- · Economy Sidewall Liner
- Spring Axles with 4" Drop
- E-Z Lube® Hubs
- · Electric Brakes with Breakaway Kit
- 2" x 6" Tube Main Rails
- · Entire Chassis Undercoated
- 16" OC Vertical Posts
- 24" OC Crossmembers
- 24" OC Tube Roof Bows
- 1-Year Limited Warranty







