

SPECIFICATIONS



	EGALX8520T3	EGALX8524T3	EGALX8528T4	EGALX8532R4	
Body: Length	20' 0"	24' 0"	28' 0"	32' 0"	
Body: Width	8' 4"	8' 4"	8' 4"	8' 4"	
Length	24' 6"	28' 6"	32' 6"	36' 6"	
Overall: Width	8' 6" 8' 8"	8' 6" 8' 9"	8' 6" 8' 10"	8' 6" 8' 10"	
Height					
Length Interior: Width	19' 8" 8' 2"	23' 8" 8' 2"	27' 8" 8' 2"	31' 8" 8' 2"	
Height	6' 10"	6' 10"	6' 10"	6' 10"	
Width Between Wheel Boxes	80"	80"	80"	80"	
Height of Wheel Box from Floor	10"	10"	11.25"	11.25"	
Platform Height	21"	21"	22"	22"	
Torflex® Suspension E-Z Lube® Axles: Qty	Tandem	Tandem	Tandem	Triple	
Electric Brakes with Breakaway Kit	Electric Drum	Electric Drum	Electric Drum	Electric Drum	
Radial Tire Size	ST205/75R15	ST225/75R15	ST235/80R16	ST235/80R16	
Tire Load Range	D	E	E	E	
Hitch Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"	
Hitch Height to Top of Ball	21"	21"	22"	22"	
Hitch Weight (% of Curb Weight)	10% - 15%	10% - 15%	10% - 15%	10% - 15%	
GVWR	9,900 lbs.	9,900 lbs.	12,000 lbs.	18,000 lbs.	
Rear Ramp Door Opening - Width x Height	96" x 83"	96" x 83"	96" x 83"	96" x 83"	
12v Male Connection	7-way	7-way	7-way	7-way	
Tube Main Rails	2"x 6"	2"x 6"	2"x 6"	2"x 6"	
Beavertail	36"	48"	48"	48"	

STANDARD FEATURES

- Flat Front/Flat Roof Design
- · All-Aluminum Frame Construction
- Aluminum Door Holdback
- Fully Integrated, All Tube, Roof and Sidewall Design
 - 16" OC Floor Crossmembers
 - 16" OC Wall Posts
 - 16" OC Roof Framing
- · .030 Aluminum Exterior Smooth Bonded
- · Bright Polished Aluminum Cap and Front Corners
- · Bright Polished Aluminum Rear Corners and Header
- · Wide Extruded Aluminum Top and Bottom Trim
- 1- Piece Aluminum Roof
- 24" ATP Stoneguard
- · Spring-Assisted Rear Ramp Door with 96" Opening
- Heavy-Duty Recessed Ramp Door Handles
- 36" Aluminum Framed Side-Entry Door with Flush Lock
- Spread Torflex® Axle Design with Aluminum Fenderettes
- · Goodyear® Radial Tires with Silver Viper Wheels*
- 12v LED Clear Lens Clearance Lights
- 12v LED Clear Lens Slim Line Tail Lights
- 12v LED Dome Lights with Wall Switch (4)
- 14" x 14" Non-Powered Roof Vent (2)
- 5,000 lbs. Square D-Rings with Welded Plate (4)
- 3/4" PlexCore[™] Flooring
- 3/8" PlexCore[™] Sidewall Liner
- · Economy Ceiling Liner
- 6-Year Limited Warranty





*Trailer features optional equipment available at additional charge.

^{*}Trailers equipped with 7,000 lb. axles do not have Goodyear® tires as standard equipment.



