

HOOKLIFTS



CiTy & T Series

- Dual pivot design (*features true dumping*)
- Operating pressure – varies by hoist – 3,300 to 4,600 PSI (*piston pump*)
- Construction – high strength, light weight, T1 steel

NOTE:
C/A, C/T and Clear Frame are subject to change. Example, add 12” for a tarp.

HOIST MODEL	CAPACITY (lb.)	HOOK HEIGHT (in.)	OPTIMUM C/A (in.)	MIN. GVWR (lb.)	CLEAR FRAME (in.)	OPTIMUM BODY LENGTHS (ft.)
CiTy	6,600	36.25	84	14,000	121	9 – 11
T 12 S	12,000	36.25	96	17,500	137	10 – 12
T 12 L	12,000	36.25	108	17,500	147	12 – 14
T 16 S	16,000	36.25	96	22,000	134	10 – 12
PHT 16 M	16,000	36.25	108	22,000	147	11 – 13
T 16 L	16,000	36.25	144	22,000	181	13 – 15
T 20 S	20,000	54	96	26,000	134	10 – 12
T 20 L	20,000	54	144	26,000	181	13 – 15
PHT 22 S	22,000	54	125	33,000	163	12 – 14
PHT 22 M	22,000	54	144	33,000	181	14 – 16
PHT 22 L	22,000	54	160	33,000	202	16 – 18