

HOOKLIFTS



www.tptruckequipment.com

1-800-255-0666



HAS Series

- Single pivot design
- Operating pressure – 2,800 PSI (*gear pump*)
- Very affordable
- Excellent for moving containers from point A to point B, limited dumping capabilities

NOTE:
C/A, C/T and Clear Frame are subject to change. Example, add 12” for a tarp.

HOIST MODEL	CAPACITY (lb.)	HOOK HEIGHT (in.)	OPTIMUM C/A (in.)	MIN. GVWR (lb.)	CLEAR FRAME (in.)	OPTIMUM BODY LENGTHS (ft.)
HAS 100 S	10,000	36.25	96	17,500	131	10 – 12
HAS 100 S SD	10,000	36.25	96	17,500	137	10 – 12
HAS 100 L	10,000	36.25	120	17,500	149	11 – 13
HAS 100 L SD	10,000	36.25	120	17,500	161	11 – 13
HAS 150	15,000	36.25	120	19,500	161	12 – 14
HAS 200 SS	20,000	36.25	120	26,000	161	12 – 14
HAS 200 S	20,000	54	120	26,000	161	12 – 14
HAS 200 M	20,000	54	144	26,000	183	13 – 15
HAS 200 L	20,000	54	144	26,000	187	14 – 16