

HOOKLIFTS



T Series *(continued)* & G Series

- Dual pivot design – G 68 features a triple pivot design (*features true dumping*)
- Operating pressure – 4,500 PSI (*piston pump*)
- Construction – high strength, light weight, T1 steel

NOTE:
C/A, C/T and Clear Frame are subject to change. Example, add 12" for a tarp.

HOIST MODEL	CAPACITY (lb.)	HOOK HEIGHT (in.)	OPTIMUM C/A (in.)	OPTIMUM C/T (in.)	MIN. GVWR (lb.)	CLEAR FRAME (in.)	OPTIMUM BODY LENGTHS (ft.)
T 29 S	29,000	54	130		33,000	167	12 – 14
T 29 ST	29,000	36.25 / 54	130		33,000	167	12 – 14
T 29 M	29,000	54	144		33,000	175	14 – 16
T 29 MT	29,000	36.25 / 54	144		33,000	175	14 – 16
T 29 L	29,000	54	160		33,000	198	16 – 18
T 29 XL	29,000	54	186		33,000	226	18 – 20
T 40 S	40,000	54 / 61.75		154	54,000	204	16 – 18
T 40 L	40,000	54 / 61.75		190	54,000	242	20 – 22
T 50	50,000	54 / 61.75		195	64,000	242	20 – 22
T 60	60,000	54 / 61.75		195	66,000	242	20 – 22
G 68	68,000	61.75		205	66,000	260	21 – 23