

TOLL FREE  
800-226-2238

VENTURO.COM



# ELECTRIC CRANES



RUGGED. RELIABLE. REAL.

MADE WITH PRIDE





## ET8K(X)



MAX. LIFT CAPACITY	MOMENT RATING	BOOM LENGTH	FEATURES	MINIMUM REQUIREMENTS	OPTIONS
2,700 lb.	8,000 ft.-lb.	6-14 ft.	65 ft. of 1/4" Aircraft-Quality Wire Rope	8,000 lb. GVWR Chassis	Radio Remote Controls
			Remote Control Pendant (25 ft. cord and quick disconnect)	Outriggers	Electric/ Hydraulic & Manual Stabilizer Packages
			Crane Weight: 650 lbs	Electrical Power Source: 12V DC	Mounting Pedestal for Platform Bodies
					Boom Rests
					Cable Overhaul Weight


### LIFTING CAPACITIES

REACH(FT.)	CAPACITY (LBS.)
3	2,700
6	1,325
10	800
14	575

ET8K BOOM EXTENSION  
POWER: 0, MANUAL: 4' + 4"

ET8KX BOOM EXTENSION  
POWER: 4', MANUAL: 4'

## ET6K




MAX. LIFT CAPACITY	MOMENT RATING	BOOM LENGTH	FEATURES	MINIMUM REQUIREMENTS	OPTIONS
2,000 lb.	6,000 ft.-lb.	6-10 ft.	50 ft. of 3/16" Aircraft-Quality Wire Rope	8,000 lb. GVWR Chassis	Radio Remote Controls
			Remote Control Pendant (20 ft. cord and quick disconnect)	Outriggers	Manual Stabilizer Packages
			Crane Weight: 380 lbs	Electrical Power Source: 12V DC	Mounting Pedestal for Platform Bodies
			Anti Two-Blocking Kit		Boom Rests

### LIFTING CAPACITIES

REACH(FT.)	CAPACITY (LBS.)
3	2,000
6	1,000
10.4	576

BOOM EXTENSION MANUAL: 4'

## DT7K




MAX. LIFT CAPACITY	MOMENT RATING	BOOM LENGTH	FEATURES	MINIMUM REQUIREMENTS	OPTIONS
2,200 lb.	7,000 ft.-lb.	6-10 ft.	Spring counterbalanced, 3-position manual boom elevation	8,000 lb. GVWR Chassis	Mounting pedestal for increased working heights
			Continuous manual rotation w/8-position base lock to hold firmly in place while in use and while traveling	Outriggers	Outrigger packages for all styles of bodies
			Load hook tie down eye built into base	Electrical Power Source: 12V DC	Quick disconnect battery cable plug/socket
			50 ft. of 3/16" Aircraft-Quality Wire Rope		
			Remote Control Pendant (15 ft. cord and quick disconnect)		
			Crane Weight: 310 lbs.		

### LIFTING CAPACITIES

REACH(FT.)	CAPACITY (LBS.)
6	1,200
8	900
10	700



# ET18KX



MAX. LIFT CAPACITY	MOMENT RATING	BOOM LENGTH	FEATURES	MINIMUM REQUIREMENTS	OPTIONS
4,500 lb.	18,000 ft.-lb.	8-16 ft.	Crane Weight: 1,020 lbs	10,500 lb. GVWR Chassis	Radio Remote Controls
			Remote Control Pendant (25 ft. cord and quick disconnect)	Outriggers: Rear	Manual Stabilizer Packages
			80 ft. of 5/16" Aircraft-Quality Wire Rope	Electrical Power Source: 12V DC	Mounting Pedestal for Platform Bodies
					Boom Rests

## LIFTING CAPACITIES

REACH(FT.)	CAPACITY (LBS.)
4	4,500
8	2,250
12	1,500
16	1,125
BOOM EXTENSION	POWER: 4' MANUAL: 4'

# ET16KX




MAX. LIFT CAPACITY	MOMENT RATING	BOOM LENGTH	FEATURES	MINIMUM REQUIREMENTS	OPTIONS
4,000 lb.	16,000 ft.-lb.	8-16 ft.	Crane Weight: 1,020 lbs	10,500 lb. GVWR Chassis	Radio Remote Controls
			Remote Control Pendant (25 ft. cord and quick disconnect)	Outriggers: Rear	Manual Stabilizer Packages
			80 ft. of 5/16" Aircraft-Quality Wire Rope	Electrical Power Source: 12V DC	Mounting Pedestal for Platform Bodies
					Boom Rests

## LIFTING CAPACITIES

REACH(FT.)	CAPACITY (LBS.)
8	2,000
12	1,250
16	900
BOOM EXTENSION	POWER: 4' MANUAL: 4'

# OUR #1 SELLING CRANE. ET12K(X)



MAX. LIFT CAPACITY	MOMENT RATING	BOOM LENGTH	FEATURES	MINIMUM REQUIREMENTS	OPTIONS
3,500 lb.	12,000 ft.-lb.	7-15 ft.	Crane Weight: 610 lbs	8,800 lb. GVWR Chassis	Radio Remote Controls
			Remote Control Pendant (25 ft. cord and quick disconnect)	Outriggers	Electric/ Hydraulic & Manual Stabilizer Packages
			65 ft. of 1/4" Aircraft-Quality Wire Rope	Electrical Power Source: 12V DC	Mounting Pedestal for Platform Bodies
					Boom Rests
					Cable Overhaul Weight

## LIFTING CAPACITIES

REACH(FT.)	CAPACITY (LBS.)
4	3,500
7	1,800
11	1,100
15	800
ET12K BOOM EXTENSION POWER: 0, MANUAL: 4' + 4'	
ET12KX BOOM EXTENSION POWER: 4', MANUAL: 4'	



# ET36KX



MAX. LIFT CAPACITY	MOMENT RATING	BOOM LENGTH	FEATURES	MINIMUM REQUIREMENTS	OPTIONS
6,000 lb.	36,000 ft.-lb.	10-20 ft.	Hexagonal Boom Construction	14,500 lb. GVWR Chassis	Radio Remote Controls
			80 ft. of 5/16" Aircraft-Quality Wire Rope	Outriggers: Rear	Electric/ Hydraulic & Manual Stabilizer Packages
			80 ft. of 5/16" Aircraft-Quality (25 ft. cord and quick disconnect)	Electrical Power Source: 12V DC	Mounting Pedestal for Platform Bodies
			Crane Weight: 1,535 lbs		Boom Rests

## LIFTING CAPACITIES

REACH(FT.)	CAPACITY (LBS.)
6	6,000
10	3,600
16	2,250
20	1,800

BOOM EXTENSION POWER: 10' MANUAL: 0'

# ET30KX(X)



MAX. LIFT CAPACITY	MOMENT RATING	BOOM LENGTH	FEATURES	MINIMUM REQUIREMENTS	OPTIONS
5,000 lb.	30,000 ft.-lb.	10-20 ft.	Hexagonal Boom Construction	11,000 lb. GVWR Chassis	Radio Remote Controls
			Loading-Holding Counterbalance Valves on All Cylinders	Outriggers: Rear	Electric/ Hydraulic & Manual Stabilizer Packages
			80 ft. of 5/16" Aircraft-Quality Wire Rope	Electrical Power Source: 12V DC	Mounting Pedestal for Platform Bodies
			Remote Control Pendant (25 ft. cord and quick disconnect)		Boom Rests
			Crane Weight: 1,535 lbs		

## LIFTING CAPACITIES

REACH(FT.)	CAPACITY (LBS.)
6	5,000
10	3,000
16	1,875
20	1,500

ET30KX BOOM EXTENSION  
POWER: 6'; MANUAL: 6' + 4"  
ET30KXX BOOM EXTENSION  
POWER: 10'

# ET25KX(X)



MAX. LIFT CAPACITY	MOMENT RATING	BOOM LENGTH	FEATURES	MINIMUM REQUIREMENTS	OPTIONS
5,000 lb.	25,000 ft.-lb.	10-20 ft.	High-Efficiency Electric Planetary Winch	10,500 lb. GVWR Chassis	Radio Remote Controls
			80 ft. of 5/16" Aircraft-Quality Wire Rope	Outriggers: Rear	Electric/ Hydraulic & Manual Stabilizer Packages
			80 ft. of 5/16" Aircraft-Quality (25 ft. cord and quick disconnect)	Electrical Power Source: 12V DC	Mounting Pedestal for Platform Bodies
			Crane Weight: 1,500 lbs		Boom Rests

## LIFTING CAPACITIES

REACH(FT.)	CAPACITY (LBS.)
5	5,000
10	2,500
16	1,575
20	1,250

ET25KX BOOM EXTENSION  
POWER: 6'; MANUAL: 6' + 4"  
ET25KXX BOOM EXTENSION  
POWER: 10'



# CRANE MODEL SELECTOR GUIDE

## HYDRAULIC TELESCOPIC CRANES

MODEL	FT. - LB. RATING	MAXIMUM LIFT CAP.	BOOM LENGTH	MINIMUM GVWR	WEIGHT (LBS.)
HT66KX-25	66,000	11,000 @ 6'	12' - 18.5' - 25'	33,000	2,500
HT50KX-25	50,000	8,000 @ 6'	12' - 18' - 25'	20,500	2,125
HT50KX	50,000	8,000 @ 6'	10' - 16' - 20'	20,500	1,925
HT40KX - 25	40,000	6,000 @ 6'	12' - 18.5' - 25'	14,500	2,100
HT40KX	40,000	6,000 @ 6'	10' - 16' - 20'	14,500	1,900
HT30KX	30,000	5,000 @ 6'	10' - 16' - 20'	11,000	1,300
HT25KX	25,000	5,000 @ 6'	10' - 16' - 20'	10,500	1,300

Selecting the correct crane for your application is critical. There are three factors that must be considered:

### 1 HOW MUCH WEIGHT WILL BE LIFTED?

Always allow a safety factor for extra weight. Crane maximum capacity shouldn't be the only determining factor. Remember that slings, blocks and any other object attached to the wire line need to be included in the weight to be lifted. And keep in mind that your maximum load may change over the years.

### 2 HOW FAR OUT FROM THE CENTER OF ROTATION IS THE LOAD?

The minimum moment rating for the crane you need is determined by multiplying the maximum reach in feet times the maximum weight in lbs. This is the best and most accurate method to decide the size of crane required for your work.

### 3 HOW OFTEN WILL A LIFT BE MADE?

This determines whether an electric or hydraulic crane should be ordered. The duty cycle of electric cranes should be under five minutes in thirty. Depending upon reservoir size and load, a hydraulic crane's operation time is nearly unlimited.

## ELECTRIC TELESCOPIC CRANES

MODEL	FT. - LB. RATING	MAXIMUM LIFT CAP.	BOOM LENGTH	MINIMUM GVWR	WEIGHT (LBS.)
ET36KX	36,000	6,000 @ 6'	10' - 16' - 20'	14,500	1,500
ET30KXX	30,000	5,000 @ 6'	10' - 16' - 20'	11,000	1,350
ET30KX	30,000	5,000 @ 6'	10' - 16' - 20'	11,000	1,350
ET25KXX	25,000	5,000 @ 5'	10' - 16' - 20'	10,500	1,350
ET25KX	25,000	5,000 @ 5'	10' - 16' - 20'	10,500	1,350
ET18KX	18,000	4,500 @ 4'	8' - 12' - 16'	10,500	1,020
ET16KX	16,000	4,000 @ 4'	8' - 12' - 16'	10,500	1,020
ET12KX	12,000	3,500 @ 4'	7' - 11' - 15'	8,800	700
ET12K	12,000	3,500 @ 4'	7' - 11' - 15'	8,800	610
ET8KX	8,000	2,700 @ 3'	6' - 10' - 14'	8,000	650
ET8K	8,000	2,700 @ 3'	6' - 10' - 14'	8,000	560
ET6K	6,000	2,000 @ 3'	6' - 10'	8,000	380
DT7K	7,000	2,200 @ 3'	6' - 10'	8,000	310

## ELECTRIC MAST CRANES

MODEL	MAXIMUM LIFT CAP.	BOOM LENGTH	ROTATION	MINIMUM GVWR	WEIGHT (LBS.)
CT310KX	1,900 @ 3'	3' - 9'3"	P	P-Ext. P-Elev.	HD/DC
CT2003FB	2,000 @ 3'	3' - 5'	M	FB	DC, AC
CT2004FB	1,500 @ 4'	4' - 7'	M	FB	DC, AC
CT2005	1,200 @ 5'	5' - 9'	M	FIXED	DC, AC
CE6K-3	2,000 @ 3'	3' - 5'	M	FB	DC, HD/DC, AC
CE6K-4	1,500 @ 4'	4' - 7'	M	FB	DC, HD/DC, AC
CE1500FB	1,500 @ 3'	3' - 5'	M	FB	DC, AC

## ELECTRIC MAST CRANES

MODEL	MINIMUM GVWR	CRANE MODELS	CAB TO AXLE	LENGTH
HT66	33,000	HT66KX	84" - 120"	11' - 14'
HT50	20,500	HT50KX	84" - 120"	11'
HT40	14,500	HT40KX, ET36KX	84"	11'
HT25	10,500	HT30KX, ET25KX	60" - 84"	9' - 11'



12110 Best Place  
Cincinnati, OH 45241

800-226-2238  
Fax 513-326-5427

[VENTURO.COM](http://VENTURO.COM)

### DISTRIBUTOR INFORMATION

Blank area for distributor information.