

EH SERIES

TANDEM AXLE EQUIPMENT HAULERS



HD Models Standard Features

- 7" Channel Main Frame
- 7" Channel Tongue
- 4" Cross Members

For hauling heavier equipment, skid steers, tractors and just about anything on wheels, our EH Series equipment trailers range from 10,000 GVWR to 14,000 GVWR. Carry up to 11,000 payload on our 14-HD units.

MODEL	EH16-10	EH18-10
BED SIZE	82"x16'	82"x18'
GVWR	10,000 LBS	10,000 LBS
EMPTY WT	2,495 LBS	2,540 LBS
DECK HEIGHT	20"	20"
TIRES	ST225/75R15D	ST225/75R15D
AXLE	5,200 LBS (2)	5,200 LBS (2)
COUPLER	2 5/16" Adjustable	2 5/16" Adjustable
JACK	8,000 LBS Side Wind Drop Leg	8,000 LBS Side Wind Drop Leg

MODEL	EH16-12	EH18-12
BED SIZE	82"x16'	82"x18'
GVWR	12,000 LBS	12,000 LBS
EMPTY WT	2,625 LBS	2,695 LBS
DECK HEIGHT	22"	22"
TIRES	ST235/80R16E	ST235/80R16E
AXLE	6,000 LBS (2)	6,000 LBS (2)
COUPLER	2 5/16" Adjustable	2 5/16" Adjustable
JACK	8,000 LBS Side Wind Drop Leg	8,000 LBS Side Wind Drop Leg

MODEL	EH18-14-HD	EH20-14-HD	EH18-16-HD	EH20-16-HD
BED SIZE	82"x18'	82"x20'	81"x18'	81"x20'
GVWR	14,000 LBS	14,000 LBS	16,000 LBS	16,000 LBS
EMPTY WT	3,000 LBS	3,300 LBS	3,300 LBS	3,600 LBS
DECK HEIGHT	23"	23"	23"	23"
TIRES	ST235/80R16E	ST235/80R16E	LT215/75R17.5H	LT215/75R17.5H
AXLE	7,000 LBS (2)	7,000 LBS (2)	8,000 LBS (2)	8,000 LBS (2)
COUPLER	2 5/16" Adjustable	2 5/16" Adjustable	2 5/16" Adjustable	2 5/16" Adjustable
JACK	12,000 LBS Side Wind Drop Leg	12,000 LBS Side Wind Drop Leg	12,000 LBS Side Wind Drop Leg	12,000 LBS Side Wind Drop Leg

Standard Colors



Standard Features

- 6" Channel Main Frame
- 6" Channel Tongue
- 3" Channel Cross Members
- Stake Pockets w/ Rub Rail
- 2" Pressure Treated Deck
- 5' Ladder Ramps
- EZ Lube Axles
- 4" Drop Axles
- Nev-R-Adjust Brakes
- Slipper Spring Suspension
- 7-Way Plug
- LED Lighting

Optional Features

- 12K Drop Leg Jack
- Spare Tire
- Spare Tire Mount
- Pallet Fork Holder
- Gooseneck
- Wood Filled Ramps
- Landscape Ramps
- Ramp Springs
- Additional D Rings
- Additional Stake Pockets
- Surge Brakes
- Aluminum Wheels

Visit www.bri-mar.com for additional specifications

